QUICK RCOLOR BLACK *400ML*

REF: 5004-001047

EN **TECHNICAL DATA SHEET**

DESCRIPTION

QUICK RCOLOR is a high quality paint formulated with nitro combined resins, in order to obtain a textured finish, suitable for bumpers.

CHARACTERISTICS

- Very fast drying.
- Lead free.
- Easy application and recoating.
- High scratch resistance after polymerization of film.
- Good adhesion.
- High coverage power.
- Excellent elasticity.

Physical properties	
Bonding agent	Nitro combined
Colour	Black
Textured	Medium
Touching drying (ASTM D-1640 ISO 1517)	10’
Total drying (ASTM D-1640 ISO 1517)	20’
Film Thickness	15 µ/coat (2 coats)
Adhesion (ASTM D-3359 ISO 2409)	4B
Theoretical coverage	2 m^2 per can 400 ml
Thinner	Butyl acetate
Shelf life	> 2 years
Recoating	After 10’
Heat painting resistance	120 °C

Application circumstances	Room temperature min: 8 °C	Surface T.: 5-50 °C	Max. humidity: 85 % R.H.P.

CAR REPAIR SYSTEM, S.A. Polígono Industrial 2 de Octubre. C./ José Muñoz, 6
18320 Santa Fe (Granada) España - Tel. 00.34. 958.431.792

Canning Charactesitics	
Nominal capacity	400 ml
Heat container resistance	< 50 °C
Propellent	DME

APPLICATION

We recommend its use for the automotive industry and specially for painting bumpers.
Automotive industry

- Shake properly the aerosol before using it for at least one minute after the agitator ball is free.
- Apply on clean and wet surfaces. Remove rust with a wire brush.
- Apply thin layers of the product for better results. It is always better applying three thin layers than a thick one, recoatable after 10 minutes with the same product.
- Do not apply on connected equipments and use the product in well ventilated areas.

STORAGE AND SHELF LIFE

12 months, if kept under proper storage conditions.

AVAILABLE PACKAGING

Code	Description	Packaging
5004-001047	QUICK RCOLOR BLACK	400ML
5004-001048	QUICK RCOLOR GREY	400ML

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet ate based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.

CAR REPAIR SYSTEM, S.A. Polígono Industrial 2 de Octubre. C./ José Muñoz, 6
18320 Santa Fe (Granada) España - Tel. 00.34. 958.431.792