



### DESCRIPTION

QUICK RCOLOR black 1000ML is a one-component product offering excellent adhesion to most plastic surfaces used in the manufacture of car bumpers (polypropylene, polycarbonate, ABS, Pohan, xenoy, rigid polyurethane, glass reinforced polyester, etc. except polyethylene and blends containing this material).

Fast drying, high adhesion, excellent resistance to washing and weathering; semi-matt appearance like original bumpers. Can be used as a one-coat topcoat.

### CHARACTERISTICS

**Colour:** black

**Chemical composition:** mixture of alkyd and acrylic resins

**Dry film appearance:** semi-matt - gloss 15 ÷ 20 (Gardner 60 °)

**Specific gravity:** 1,13 kg / l (± 0,02)

**Viscosity:** 3000 ÷ 5000 mPas Brookfield

**Practical coverage rate:** 3 ÷ 5 m<sup>2</sup> / l depending on the thickness applied.

**Shelf life:** 24 months in original sealed container.

**NB:** Data recorded at 20 ° C (68 ° F)

**Note\*:** The product complies with Directive 2004/42 / EC-IIIB (e) Maximum limit value of VOC: 840 g / l

### APPLICATION

- **Surface preparation:** The surface to be treated must be dry, clean and free of oil, bitumen and mud stains. Wipe off any traces of silicone or polishing wax.
- **Preparation of the product:** Stir well to uniform the colour and consistency.
- **Application method:** - air mixing gun with nozzle 1,7 ÷ 1,9 mm and pressure 2 ÷ 3 bar.
- **Reduction:** 10-15% with DILUYENTE CARS
- **Suggested thickness:** dry film 50 ÷ 100 mic. (high thickness is not necessary).
- **Air drying (20 ° C - 65% RH) with thickness 80÷100 mic:**
  - **Touch dry:** 30 minutes
  - **Continuous drying:** 8 hours
- **Recoating:** after 4-6 hours

## STORAGE AND SHELF LIFE

12 months, if kept under proper storage conditions.

## AVAILABLE PACKAGING

Code	Description	Packaging
5004-002047	QUICK RCOLOR BLACK	1000ML

\*For more information about our products or means of application, please visit our website [www.carrepairsystem.eu](http://www.carrepairsystem.eu) or send us an e-mail to [info@carrepairsystem.eu](mailto:info@carrepairsystem.eu)

*The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.*