



DESCRIPTION

QUICK WHEEL SILVER, Nitro-based, plastified, single-component acrylic paint for final retouching of surfaces.

TECHNICAL DATA

Feature of painting liquid to 20°C	LIMITS	UNITS
Viscosity	100	KU to 20 °C
Density	0.971+/-0.01	g/ml
Solid	31.2+/-2	%
Flash point	12	°C
Stability	12	Months

Application features

Mixture ratio	One component	
Hardener to use		---
Diluent to use	30+/-5	%
Viscosity of application	18-20	S(CF4 20°C)
Pot life	--	--
Application system	Aerographic	
Support	Laminated steel	
Drying	20 min.	to 25°C

Properties of the film polymerised

Thickness	35+/-10	microns
Adherence	100	%
Brightness	60-65	% to 60°
Colour	Silver	
Hardness Persoz	>180	S
Elasticity to bending	9	mm

Elasticity to the embossing	5	mm
Impact resistance	30 cm x 12.5 mm	Weight 1 kg
Salt spray chamber resistance	---	hours
Moist chamber resistance	--- h	hours

SECURITY INFORMATION

See Safety Data Sheet.

AVAILABLE PACKAGING

Code	Description	Packaging
5011-001136	QUICK WHEEL SILVER	500 ML
5004-001136	QUICK WHEEL SILVER	1000 ML

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.