



DESCRIPTION

Very quick-drying thermoplastic acrylic enamel, formulated with prime quality resins.

APPLICATION

Automotive Industry.

INSTRUCTIONS OF USE

- Shake properly the aerosol before using it for at least one minute after the agitator ball is free.
- Apply on clean and wet surfaces. Remove rust with a wire brush. Apply an anchor-base layer on plastics and polyesters.
- Apply thin layers of the product for better results. It is always better applying three thin layers than a thick one, recoatable after 10 minutes with the same product.
- Invert the aerosol to purge the valve after using it. If the actuator gets blocked, replace it by a new one.
- Do not apply on connected equipments and use the product in well ventilated areas.
- Request Safety Data Sheets.

FEATURES

- Fast drying.
- Good adhesion.
- Good hardening.
- Great bright durability.
- Totally lead free.

TECHNICAL DATA

PHYSICAL CHARACTERISTICS

| | | | |
|-------------------------------------|---------------------------------------|-----------------------------|--------------------------|
| Composition | Thermoplastic modified acrylic | | |
| Colour | Grey aluminium | | |
| Touch Drying (ASTM D-1640 ISO 1517) | 10' | | |
| Total drying (ASTM D-1640 ISO 1517) | 30' | | |
| Thickness of dry layer | 15 µ/layer (2 layers) | | |
| Adhesion (ASTM-3359 ISO 2409) | 2B | | |
| Theoretical efficiency | 2-2.5 m ² per spray 400 ml | | |
| Thinner | Butyl acetate | | |
| Shelf life | Minimum 2 years | | |
| Overpaintable | After 10 min. | | |
| Application conditions | Min room temperature: 8°C | Surface temperature: 5-50°C | Max. humidity: 85% R.H.P |

CONTAINER CHARACTERISTICS

| | |
|---------------------------|------------------------------------|
| Nominal capacity | 500 ml |
| Container heat-resistance | < 50°C |
| Propellant | GLP C ₃ -C ₄ |
| VOC | 617 g/l |

SECURITY INFORMATION

See Safety Data Sheet.

AVAILABLE PACKAGING

| Code | Description | Packaging |
|-------------|--------------------|-----------|
| 5011-001136 | QUICK WHEEL SILVER | 500 ML |
| 5004-001136 | QUICK WHEEL SILVER | 1000 ML |

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.