



## TECHNICAL DATA SHEET



### DESCRIPTION

QUICK MIX EXPRESS 50 ML is a two-component adhesive especially suitable for the rapid repair of all types of applications. It offers excellent adhesion on different surfaces such as plastic, metal, wood, etc. The product dries very fast so that the repaired part can be reused after more than 10 minutes.

Due to its special formulation, QUICK MIX EXPRESS 50 ML allows an extremely strong bond. Due to its flexibility, it can be used for all kinds of applications.

Thanks to its unique properties, joints that were previously impossible can be made. In addition, QUICK MIX EXPRESS 50 ML makes it possible to repair parts that would normally be thrown away. It can also be used for all kinds of urgent repairs.

QUICK MIX EXPRESS 50 ML has excellent creep resistance and a long spray time. Use the product for bonding vertical surfaces that cannot be glued or moulded at once.

Packaged in a special cartridge for two-component product, easy to use and to apply with a spray gun. The special mixing nozzle ensures a good mixing ratio at all times and prevents the product remaining in the cartridge from hardening. This is why a cartridge of QUICK MIX EXPRESS 50 ML can be stored for a long time.

### CHARACTERISTICS

- Very good adhesion on many surfaces
- Very fast drying
- Very fast manual resistance
- Creep resistance
- Bi-component product for very fast bonding
- Practical double cartridge for use with mixing cannulas for precise dosing.

**SECURITY INFORMATION**

See Security data sheet.

**STORAGE AND SHELF LIFE**

The shelf life of QUICK MIX EXPRESS 50 ML is 12 months from the date of production, as long as it is stored in a cool and dry place, temperature varying between +10°C and 25°C. The expiry date is indicated on the label.

**AVAILABLE PACKAGING**

Code	Description	Packaging
5006-001096	QUICK MIX EXPRESS	50ML

\*For more information about our products or means of application, please visit our website [www.carrepairsystem.eu](http://www.carrepairsystem.eu) or send us an e-mail to [info@carrepairsystem.eu](mailto:info@carrepairsystem.eu)

*The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.*