

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 30/12/2021 Page 1 / 13

	QUICK WHEEL SILVER 1000ML Code: 5004-001136	
--	------------------------------------------------	--

Version: 1 Date of compilation: 30/12/2021

Date of printing: 30/12/2021

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	PRODUCT IDENTIFIER: QUICK WHEEL SILVER 1000ML UFI: 0D4F-1HMU-FCOH-CWU8 Code: 5004-001136
1.2	RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> [X] Industrial [X] Professional Liquid paint. <u>Relevant product types:</u> Paints and varnishes, industrial, professional. <u>Sectors of use:</u> Industrial manufacturing (SU3). Professional uses (SU22). <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as 'Intended or identified uses'. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Contains CMR substances, categories 1A or 1B: Restricted to professional users. Forbidden to the general public. The restrictions do not apply to storage, keeping, treatment, filling into containers, or transfer from one container to another of the substances for export. See entry 28 and/or 29 and/or 30 in the Annex of the Regulation (EC) No. 552/2009~276/2010.
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: CAR REPAIR SYSTEM S.A. Pol. Ind. 2 de Octubre. C/ Jose Muñoz, 6 - E-18320 - Santa Fe - Granada (Española) Phone: +34 95 8431792 <u>E-mail address of the person responsible for the Safety Data Sheet:</u> info@carrepairsystem.eu
1.4	EMERGENCY TELEPHONE NUMBER: +34 95 8431792 (L-J 8:30-14 / 15-18 h. V 8:30-14:30 h.) (working hours)

SECTION 2 : HAZARDS IDENTIFICATION




2.1

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

Classification in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP):





















DANGER: Flam. Liq. 2:H225 | Skin Irrit. 2:H315 | Eye Irrit. 2:H319 | Skin Sens. 1:H317 | Repr. 1B:H360 | STOT SE (irrit.) 3:H335 | STOT SE (narcosis) 3:H336 | STOT RE 2:H373

Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
<u>Physicochemical:</u> 	Flam. Liq. 2:H225 Skin Irrit. 2:H315 Eye Irrit. 2:H319 Skin Sens. 1:H317	a) Cat.2 c) Cat.2 c) Cat.2 c) Cat.1	- Skin Eyes Skin	- Skin Eyes Skin	- Irritation Irritation Allergy
<u>Human health:</u>  	Repr. 1B:H360 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 STOT RE 2:H373	c) Cat.1B c) Cat.3 c) Cat.3 c) Cat.2	. Inhalation Inhalation .	Reproductive system Respiratory tract CNS Systemic	- Irritation Narcosis Damage
<u>Environment:</u> Not classified					

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2	LABEL ELEMENTS: This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP) <u>Hazard statements:</u> H225 Highly flammable liquid and vapour. H360 May damage fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H317 May cause an allergic skin reaction. <u>Precautionary statements:</u>
-----	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	QUICK WHEEL SILVER 1000ML Code: 5004-001136	  
	<p>P102 P201-P202-P405 P210 P280F P363 P303+P361+P353-P352-P312 P304+P340 P305+P351+P338 P501b</p> <p>Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Store locked up. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash with plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents/container to hazardous or special waste collection point.</p> <p><u>Supplementary statements:</u> None. <u>Substances that contribute to classification:</u> Xylene (mixture of isomers) n-butyl acetate Isopropyl alcohol Dicyclohexyl phthalate</p>	
2.3	<p><u>OTHER HAZARDS:</u> Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: <u>Other physicochemical hazards:</u> Vapours may form with air a mixture potentially flammable or explosive. <u>Other adverse human health effects:</u> Prolonged contact may cause skin dryness. <u>Other negative environmental effects:</u> Does not contain substances that fulfil the PBT/vPvB criteria.</p>	
SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS		
3.1	<p><u>SUBSTANCES:</u> Not applicable (mixture).</p>	
3.2	<p><u>MIXTURES:</u> This product is a mixture. <u>Chemical description:</u> Mixture of pigments, resins and additives in organic solvents.</p> <p><u>INGREDIENTS:</u></p>	
	<p>30 < 40 %    <u>Xylene (mixture of isomers)</u> CAS: 1330-20-7 , EC: 215-535-7 REACH: 01-2119488216-32 Autoclassified < REACH CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 Acute Tox. (skin) 4:H312 Skin Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOT RE 2:H373IE Asp. Tox. 1:H304 Aquatic Chronic 3:H412</p>	
	<p>15 < 20 %   <u>n-butyl acetate</u> CAS: 123-86-4 , EC: 204-658-1 REACH: 01-2119485493-29 Index No. 607-025-00-1 < REACH / ATP01 CLP: Warning: Flam. Liq. 3:H226 STOT SE (narcosis) 3:H336 EUH066</p>	
	<p>5 < 10 %   <u>Isopropyl alcohol</u> CAS: 67-63-0 , EC: 200-661-7 REACH: 01-2119457558-25 Index No. 603-117-00-0 < REACH / ATP01 CLP: Danger: Flam. Liq. 2:H225 Eye Irrit. 2:H319 STOT SE (narcosis) 3:H336</p>	
	<p>2,5 < 5 %  <u>Aluminium powder (phlegmatized)</u> CAS: 7429-90-5 , EC: 231-072-3 REACH: 01-2119529243-45 Index No. 013-002-00-1 < REACH / ATP01 CLP: Danger: Flam. Sol. 2:H228 Water-react. 2:H261 (Note T)</p>	
	<p>1 < 2 %   <u>Dicyclohexyl phthalate</u> CAS: 84-61-7 , EC: 201-545-9 REACH: 01-2119978223-34 < REACH CLP: Danger: Skin Sens. 1:H317 Repr. 1B:H360D Aquatic Chronic 3:H412</p>	
	<p>1 < 2 %    <u>Naphtha (petroleum), hydrodesulfurized heavy</u> CAS: 64742-82-1 , EC: 265-185-4 REACH: 01-2119490979-12 Index No. 649-330-00-2 < REACH / ATP01 CLP: Danger: Flam. Liq. 3:H226 Skin Irrit. 2:H315 STOT SE (narcosis) 3:H336 (Note H,P) Asp. Tox. 1:H304 Aquatic Chronic 2:H411</p>	
	<p>1 < 2 %    <u>Solvent naphtha (petroleum), light aromatic</u> CAS: 64742-95-6 , EC: 265-199-0 REACH: 01-2119486773-24 Index No. 649-356-00-4 < REACH / ATP01 CLP: Danger: Flam. Liq. 3:H226 Skin Irrit. 2:H315 STOT SE (narcosis) 3:H336 (Note H,P) Asp. Tox. 1:H304 Aquatic Chronic 2:H411</p>	



QUICK WHEEL SILVER 1000ML
Code: 5004-001136

Impurities:

Content of benzene < 0.1%.

Stabilizers:

None

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 08/07/2021.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

Dicyclohexyl phthalate, CMR/Repr.Cat. 1B (Article 57c), Endocrine disrupting properties having probable serious effects to human health (Article 57f), Decision: ED/61/2018.

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.

SECTION 4 : FIRST AID MEASURES**4.1 DESCRIPTION OF FIRST-AID MEASURES:**

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposureSymptoms and effects, acute and delayedDescription of first-aid measuresInhalation:

Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.

Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.

Skin:

Skin contact causes redness. Prolonged contact may cause skin dryness.

Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners. In the case of skin reddening or rashes, contact a doctor immediately.

Eyes:

Contact with the eyes produces redness and pain.

Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.

Ingestion:

If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.

If swallowed, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.





Antidotes and contraindications: Specific antidote not known.



SECTION 5 : FIRE-FIGHTING MEASURES**5.1 EXTINGUISHING MEDIA:**

Extinguishing powder or CO₂. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products may be a hazard to health.

	QUICK WHEEL SILVER 1000ML Code: 5004-001136	  												
5.3	<p>ADVICE FOR FIREFIGHTERS: <u>Special protective equipment:</u> Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. <u>Other recommendations:</u> Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.</p>													
SECTION 6 : ACCIDENTAL RELEASE MEASURES														
6.1	<p>PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.</p>													
6.2	<p>ENVIRONMENTAL PRECAUTIONS: Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.</p>													
6.3	<p>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Avoid use of solvents. Keep the remains in a closed container.</p>													
6.4	<p>REFERENCE TO OTHER SECTIONS: For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For waste disposal, follow the recommendations in section 13.</p>													
SECTION 7 : HANDLING AND STORAGE														
7.1	<p>PRECAUTIONS FOR SAFE HANDLING: Comply with the existing legislation on health and safety at work. <u>General recommendations:</u> Avoid any type of leakage or escape. Keep the container tightly closed. <u>Recommendations for the prevention of fire and explosion risks:</u> Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.</p> <table><tr><td>- Flash point</td><td>:</td><td>22. °C</td><td>CLP 2.6.4.3.</td></tr><tr><td>- Autoignition temperature</td><td>:</td><td>188* °C</td><td></td></tr><tr><td>- Lower/upper flammability or explosive limits</td><td>:</td><td>1.2* - 8.0* % Volume 25°C</td><td></td></tr></table> <p><u>Recommendations for the prevention of toxicological risks:</u> Pregnant women should not be employed in any process in which this product is used. Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8. <u>Recommendations for the prevention of environmental contamination:</u> It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.</p>		- Flash point	:	22. °C	CLP 2.6.4.3.	- Autoignition temperature	:	188* °C		- Lower/upper flammability or explosive limits	:	1.2* - 8.0* % Volume 25°C	
- Flash point	:	22. °C	CLP 2.6.4.3.											
- Autoignition temperature	:	188* °C												
- Lower/upper flammability or explosive limits	:	1.2* - 8.0* % Volume 25°C												
7.2	<p>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.</p> <table><tr><td><u>Class of storage</u></td><td>:</td><td>According to current legislation.</td></tr><tr><td><u>Temperature interval</u></td><td>:</td><td>min: 5. °C, max: 35. °C (recommended).</td></tr></table> <p><u>Incompatible materials:</u> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. <u>Type of packaging:</u> According to current legislation. <u>Limit quantity (Seveso III):</u> Directive 2012/18/EU: - Named dangerous substances/mixtures: None - Hazard categories and lower-/upperthreshold quantities in tonnes (t): · Physical hazards: Highly flammable liquid and vapour (P5c) (5000t/50000t). · Health hazards: Not applicable · Environmental hazards: Not applicable · Other hazards: Not applicable. - Threshold quantity for the application of lower-tier requirements: 5000 tons - Threshold quantity for the application of upper-tier requirements: 50000 tons - Remarks: The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.</p>		<u>Class of storage</u>	:	According to current legislation.	<u>Temperature interval</u>	:	min: 5. °C, max: 35. °C (recommended).						
<u>Class of storage</u>	:	According to current legislation.												
<u>Temperature interval</u>	:	min: 5. °C, max: 35. °C (recommended).												

	QUICK WHEEL SILVER 1000ML Code: 5004-001136	
----------------------------------------------------------------------------------	-------------------------------------------------------	-------------------------------------------------------------------------------------

- 7.3 **SPECIFIC END USES:**
For the use of this product particular recommendations apart from that already indicated are not available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 **CONTROL PARAMETERS:**
If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2020	Year	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m ³	ppm	mg/m ³	
Xylene	1996	100.	434.	150.	651.	A4 , BEI
n-butyl acetate	2015	50.	237.	150.	713.	
Isopropyl alcohol	2001	200.	491.	400.	982.	A4 , BEI
Aluminium powder (phlegmatized)	2007	-	1.0	-	-	Breathable dust A4
Naphtha (petroleum), hydrodesulfurized heavy		100.	525.	-	-	Recommended
Solvent naphtha (petroleum), light aromatic		50.	290.	-	-	Internal value

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

A4 - Non classified as carcinogenic in humans.

BEI - Biological exposure index (biological monitoring).

BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

- Xylenes (technical or commercial grade) (2011): Biological determinant: methylhippuric acids in urine, BEI: 1.5 g/g creatinine, Sampling time: end of shift (2).

- 2-propanol (2005): Biological determinant: acetone in urine, BEI: 40 mg/l, Sampling time: end of shift at end of workweek (4), Notation: (B) (Ns).

(2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases.

(4) The value refers to the difference of the results of the samples taken at the end and at the beginning of the working day.

(B) Background. The determinant may be present in biological specimens collected from subjects who have not been occupationally exposed, at a concentration that could affect interpretation of the result. Such background concentrations are incorporated in (Ns) Non-specific. The determinant is non-specific, since it is also observed after exposure to other chemicals.

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers: - Systemic effects, acute and chronic:	DNEL Inhalation		DNEL Cutaneous		DNEL Oral	
	mg/m ³		mg/kg bw/d		mg/kg bw/d	
Xylene (mixture of isomers)	289. (a)	77.0 (c)	s/r (a)	180. (c)	- (a)	- (c)
n-butyl acetate	960. (a)	480. (c)	11.0 (a)	11.0 (c)	- (a)	- (c)
Isopropyl alcohol	- (a)	500. (c)	- (a)	888. (c)	- (a)	- (c)
Aluminium powder (phlegmatized)	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Dicyclohexyl phthalate	35.2 (a)	39.2 (c)	0.500 (a)	0.500 (c)	- (a)	- (c)
Naphtha (petroleum), hydrodesulfurized heavy	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Solvent naphtha (petroleum), light aromatic	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).



QUICK WHEEL SILVER 1000ML
Code: 5004-001136

**DERIVED NO-EFFECT LEVEL (DNEL):**

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers:**- Systemic effects, acute and chronic:**

Xylene (mixture of isomers)
n-butyl acetate
Isopropyl alcohol
Aluminium powder (phlegmatized)
Dicyclohexyl phthalate
Naphtha (petroleum), hydrodesulfurized heavy
Solvent naphtha (petroleum), light aromatic

DNEL Inhalationmg/m³

289. (a) 77.0 (c)
960. (a) 480. (c)
- (a) 500. (c)
- (a) - (c)
35.2 (a) 39.2 (c)
- (a) - (c)
- (a) - (c)

DNEL Cutaneous

mg/kg bw/d

s/r (a) 180. (c)
11.0 (a) 11.0 (c)
- (a) 888. (c)
- (a) - (c)
0.500 (a) 0.500 (c)
- (a) - (c)
- (a) - (c)

DNEL Oral

mg/kg bw/d

- (a) - (c)
- (a) - (c)
- (a) - (c)
- (a) - (c)
- (a) - (c)
- (a) - (c)
- (a) - (c)

Derived no-effect level, workers:**- Local effects, acute and chronic:**

Xylene (mixture of isomers)
n-butyl acetate
Isopropyl alcohol
Aluminium powder (phlegmatized)
Dicyclohexyl phthalate
Naphtha (petroleum), hydrodesulfurized heavy
Solvent naphtha (petroleum), light aromatic

DNEL Inhalationmg/m³

289. (a) s/r (c)
960. (a) 480. (c)
- (a) - (c)
- (a) 3.75 (c)
s/r (a) s/r (c)
- (a) - (c)
- (a) - (c)

DNEL Cutaneousmg/cm²

s/r (a) s/r (c)
s/r (a) s/r (c)
- (a) - (c)
- (a) - (c)
s/r (a) s/r (c)
- (a) - (c)
- (a) - (c)

DNEL Eyesmg/cm²

- (a) - (c)
s/r (a) - (c)
- (a) - (c)
- (a) - (c)
s/r (a) - (c)
- (a) - (c)
- (a) - (c)

Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

PREDICTED NO-EFFECT CONCENTRATION (PNEC):**Predicted no-effect concentration, aquatic organisms:****- Fresh water, marine water and intermittent release:**

Xylene (mixture of isomers)
n-butyl acetate
Isopropyl alcohol
Aluminium powder (phlegmatized)
Dicyclohexyl phthalate
Naphtha (petroleum), hydrodesulfurized heavy
Solvent naphtha (petroleum), light aromatic

PNEC Fresh water

mg/l

0.327
0.180
141.
0.0749
0.00362
uvcb
uvcb

PNEC Marine

mg/l

0.327
0.0180
141.
-
0.000362
uvcb
uvcb

PNEC Intermittent

mg/l

0.327
0.360
141.
-
0.0362
uvcb
uvcb

- Wastewater treatment plants (STP) and sediments in fresh- and marine water:

Xylene (mixture of isomers)
n-butyl acetate
Isopropyl alcohol
Aluminium powder (phlegmatized)
Dicyclohexyl phthalate
Naphtha (petroleum), hydrodesulfurized heavy
Solvent naphtha (petroleum), light aromatic

PNEC STP

mg/l

6.58
35.6
2251.
20.0
10.0
uvcb
uvcb

PNEC Sediments

mg/kg dw/d

12.5
0.981
552.
-
1.06
uvcb
uvcb

PNEC Sediments

mg/kg dw/d

12.5
0.0981
552.
-
0.106
uvcb
uvcb

Predicted no-effect concentration, terrestrial organisms:**- Air, soil and effects for predators and humans:**

Xylene (mixture of isomers)
n-butyl acetate
Isopropyl alcohol
Aluminium powder (phlegmatized)
Dicyclohexyl phthalate
Naphtha (petroleum), hydrodesulfurized heavy
Solvent naphtha (petroleum), light aromatic

PNEC Airmg/m³

-
s/r
-
-
s/r
uvcb
uvcb

PNEC Soil

mg/kg dw/d

2.31
0.0903
28.0
-
0.210
uvcb
uvcb

PNEC Oral

mg/kg dw/d




-
n/b
160.
-
133000.
uvcb
uvcb

(-) - PNEC not available (without data of registration REACH).

s/r - PNEC not derived (not identified hazard).

n/b - PNEC not derived (not bioaccumulative potential).

uvcb - The substance has an unknown or variable composition (UVCB). The conventional methods to derive the PNEC are not appropriate and it is not possible to identify a single PNEC representative for these substances, and therefore not used in calculations for risk assessment.

<div></div> <div>QUICK WHEEL SILVER 1000ML Code: 5004-001136</div>		<div></div>														
8.2	<div>EXPOSURE CONTROLS:</div> <div>ENGINEERING MEASURES:</div> <div><div></div><div>Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.</div></div> <div>Protection of respiratory system: Avoid the inhalation of vapours.</div> <div>Protection of eyes and face: It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area.</div> <div>Protection of hands and skin: It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.</div> <div>OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:</div> <div>As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.</div> <table><tr><td><div>Mask:</div><div></div><div>✓</div></td><td>A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.</td></tr><tr><td><div>Safety goggles:</div><div></div><div>✓</div></td><td>Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.</td></tr><tr><td><div>Face shield:</div></td><td>No.</td></tr><tr><td><div>Gloves:</div><div></div><div>✓</div></td><td>Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.</td></tr><tr><td><div>Boots:</div></td><td>No.</td></tr><tr><td><div>Apron:</div></td><td>Advisable.</td></tr><tr><td><div>Clothing:</div></td><td>Advisable.</td></tr></table> <div>Thermal hazards:</div> <div>Not applicable (the product is handled at room temperature).</div> <div>ENVIRONMENTAL EXPOSURE CONTROLS:</div> <div>Avoid any spillage in the environment. Avoid any release into the atmosphere.</div> <div>Spills on the soil: Prevent contamination of soil.</div> <div>Spills in water: Do not allow to escape into drains, sewers or water courses.</div> <div>- Water Management Act: This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.</div> <div>Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.</div> <div>- VOC (industrial installations): If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents : 64.3% Weight , VOC (supply) : 64.3% Weight , VOC : 48.8% C (expressed as carbon) , Molecular weight (average) : 100.6 , Number C atoms (average) : 6.4.</div>		<div>Mask:</div> <div></div> <div>✓</div>	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.	<div>Safety goggles:</div> <div></div> <div>✓</div>	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.	<div>Face shield:</div>	No.	<div>Gloves:</div> <div></div> <div>✓</div>	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.	<div>Boots:</div>	No.	<div>Apron:</div>	Advisable.	<div>Clothing:</div>	Advisable.
<div>Mask:</div> <div></div> <div>✓</div>	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.															
<div>Safety goggles:</div> <div></div> <div>✓</div>	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.															
<div>Face shield:</div>	No.															
<div>Gloves:</div> <div></div> <div>✓</div>	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.															
<div>Boots:</div>	No.															
<div>Apron:</div>	Advisable.															
<div>Clothing:</div>	Advisable.															

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 30/12/2021 Page 8 / 13

QUICK WHEEL SILVER 1000ML
Code: 5004-001136**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:**Appearance

- Physical state : Liquid.
- Colour : Silver.
- Odour : Characteristic.

pH-value

- pH : Not applicable (non-aqueous media).

Change of state

- Melting point : Not applicable (mixture).
- Boiling interval : 82. - 160* °C at 760 mmHg

Density

- Vapour density : 2.89* at 20°C 1 atm. Relative air
- Relative density : 0.978 ± 0.97 at 20/4°C Relative water

StabilityViscosity:

- Dynamic viscosity : 1580. cps 20°C
- Kinematic viscosity : 550. mm²/s at 40°C
- Viscosity (Krebs-Stormer) : 100. ± 100. KU 20°C

Volatility:

- Vapour pressure : 12. mmHg at 20°C
- Vapour pressure : 8.5* kPa at 50°C

Solubility(ies)

- Solubility in water : Not applicable
- Partition coefficient: n-octanol/water : Not applicable (mixture).

Flammability:

- Flash point : 22. °C CLP 2.6.4.3.
- Lower/upper flammability or explosive limits : 1.2* - 8.0* % Volume 25°C
- Autoignition temperature : 188* °C

Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:

- Solids : 38. % Weight
- VOC (supply) : 64.3 % Weight
- VOC (supply) : 606.4 g/l

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10 : STABILITY AND REACTIVITY**10.1 REACTIVITY:**Corrosivity to metals: It is not corrosive to metals.Pyrophorical properties: It is not pyrophoric.**10.2 CHEMICAL STABILITY:**

Stable under recommended storage and handling conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with reducing agents, oxidizing agents, acids, alkalis, peroxides.

10.4 CONDITIONS TO AVOID:Heat: Keep away from sources of heat.Light: If possible, avoid direct contact with sunlight.Air: The product is not affected by exposure to air, but should not be left the containers open.Humidity: Avoid extreme humidity conditions.Pressure: Not relevant.Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.**10.5 INCOMPATIBLE MATERIALS:**

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.



QUICK WHEEL SILVER 1000ML
Code: 5004-001136



SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations

for individual ingredients :

Xylene (mixture of isomers)

n-butyl acetate

Isopropyl alcohol

Aluminium powder (phlegmatized)

Dicyclohexyl phthalate

Naphtha (petroleum), hydrodesulfurized heavy

Solvent naphtha (petroleum), light aromatic

LD50 (OECD 401)
mg/kg bw oral

4300. Rat

10768. Rat

5045. Rat

15900. Rat

> 2000. Rat

6000. Rat

3900. Rat

LD50 (OECD 402)
mg/kg bw cutaneous

1700. Rabbit

17600. Rabbit

12800. Rabbit

> 2000. Rat

3000. Rat

3160. Rabbit

LC50 (OECD 403)
mg/m³-4h inhalation

> 22080. Rat

> 23400. Rat

> 72600. Rat

> 888. Rat

> 7630. Rat

Estimates of acute toxicity (ATE)

for individual ingredients :

Xylene (mixture of isomers)

ATE

mg/kg bw oral

-

ATE

mg/kg bw cutaneous

1100.*

ATE

mg/m³-4h inhalation

11000.* Vapours

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
<u>Inhalation:</u> Not classified	ATE > 20000 mg/m ³	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<u>Skin:</u> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
<u>Ingestion:</u> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Respiratory corrosion/irritation:</u> 	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 1.2.6. 3.8.3.4.
<u>Skin corrosion/irritation:</u> 	Skin 	Cat.2	IRRITANT: Causes skin irritation.	GHS/CLP 3.2.3.3.
<u>Serious eye damage/irritation:</u> 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
<u>Skin sensitisation:</u> 	Skin 	Cat.1	SENSITISING: May cause an allergic skin reaction.	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.



QUICK WHEEL SILVER 1000ML
Code: 5004-001136

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Aspiration hazard:</u> Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Systemic:</u> 	RE	Systemic 	Cat.2	HARMFUL: May cause damage to organs through prolonged or repeated exposure.	GHS/CLP 3.8.3.4.
<u>Respiratory:</u> 	SE	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 3.8.3.4.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

Carcinogenic effects: It is not considered as a carcinogenic product.

Genotoxicity: It is not considered as a mutagenic product.

Toxicity for reproduction:

This preparation contains the following ingredients which can be toxic for human reproduction:

Dicyclohexyl phthalate (Cat.1B)

Effects via lactation: Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat and other effects may be the same as described in the exposure to vapours.

Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption: Not available.

Basic toxicokinetics: Not available.

ADDITIONAL INFORMATION:

Not available.

SECTION 12 : ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

12.1 TOXICITY:Acute toxicity in aquatic environment

for individual ingredients :

Xylene (mixture of isomers)

n-butyl acetate

Isopropyl alcohol

Aluminium powder (phlegmatized)

Dicyclohexyl phthalate

Naphtha (petroleum), hydrodesulfurized heavy

Solvent naphtha (petroleum), light aromatic

LC50 (OECD 203)
mg/l-96hours

> 13. Fishes

> 18. Fishes

9640. Fishes

220. Fishes

> 2.0 Fishes

> 2.6 Fishes

> 9.2 Fishes

EC50 (OECD 202)
mg/l-48hours

> 16. Daphnia

> 44. Daphnia

13300. Daphnia

> 100. Daphnia

> 2.3 Daphnia

> 6.1 Daphnia

EC50 (OECD 201)
mg/l-72hours

> 10. Algae

675. Algae

> 1000. Algae

> 100. Algae

> 10. Algae

No observed effect concentration

n-butyl acetate

NOEC (OECD 210)
mg/l-28days

NOEC (OECD 211)
mg/l-21days

23. Daphnia

NOEC (OECD 201)
mg/l-72hours

Lowest observed effect concentration

Not available



QUICK WHEEL SILVER 1000ML
Code: 5004-001136



ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
<u>Acute aquatic toxicity:</u> Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
<u>Chronic aquatic toxicity:</u> Not classified	-	Not classified as a dangerous product with chronic toxicity to aquatic life with long lasting effects (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.4.
CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.			
CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.			

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

<u>Aerobic biodegradation</u> for individual ingredients :	<u>DOO</u> mgO ₂ /g	<u>%DBO/DOO</u> 5 days 14 days 28 days	<u>Biodegradability</u>
Xylene (mixture of isomers)	2620.	~ 52. ~ 81. ~ 88.	Easy
n-butyl acetate	2204.	~ 80. ~ 82. ~ 83.	Easy
Isopropyl alcohol	2396.		Easy
Dicyclohexyl phthalate			Easy
Naphtha (petroleum), hydrodesulfurized heavy		24. 52. 74.	Easy
Solvent naphtha (petroleum), light aromatic	3195.		Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

12.3 BIOACCUMULATIVE POTENTIAL:

May bioaccumulate.

<u>Bioaccumulation</u> for individual ingredients :	<u>log Pow</u>	<u>BCF</u> L/kg	<u>Potential</u>
Xylene (mixture of isomers)	3.16	56. (calculated)	Low
n-butyl acetate	1.81	6.9 (calculated)	Not bioaccumulative.
Isopropyl alcohol	0.0500	3.2 (calculated)	Not bioaccumulative.
Dicyclohexyl phthalate	4.82	> 100. (calculated)	Low
Naphtha (petroleum), hydrodesulfurized heavy	5.65	> 100. (calculated)	Low
Solvent naphtha (petroleum), light aromatic	3.30	70. (calculated)	Low

12.4 MOBILITY IN SOIL:

Not available.

<u>Mobility</u> for individual ingredients :	<u>log P_{oc}</u>	<u>Constant of Henry</u> Pa·m ³ /mol 20°C	<u>Potential</u>
Xylene (mixture of isomers)	2.25	660. (calculated)	Low
n-butyl acetate	1.84	28. (calculated)	Not bioaccumulative.
Isopropyl alcohol	0.540		Not bioaccumulative.
Dicyclohexyl phthalate	4.22		Low
Naphtha (petroleum), hydrodesulfurized heavy	4.90		Low
Solvent naphtha (petroleum), light aromatic	2.96	440. (calculated)	Low

12.5 RESULTS OF PBT AND VPVB ASSESMENT: Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 OTHER ADVERSE EFFECTS:

Ozone depletion potential: Not available.

Photochemical ozone creation potential: Not available.

Earth global warming potential: In case of fire or incineration liberates CO₂.

Endocrine disrupting potential: Not available.

SECTION 13 : DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014:

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.








Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 30/12/2021 Page 12 / 13

	QUICK WHEEL SILVER 1000ML Code: 5004-001136	  
SECTION 14 : TRANSPORT INFORMATION		
14.1	<u>UN NUMBER:</u> 1263	
14.2	<u>UN PROPER SHIPPING NAME:</u> PAINT	
14.3	<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p><u>TRANSPORT HAZARD CLASS(ES):</u></p> <p><u>Transport by road (ADR 2021) and</u> <u>Transport by rail (RID 2021):</u></p> <ul style="list-style-type: none"> - Class: 3 - Packing group: III - Classification code: F1 - Tunnel restriction code: (D/E) - Transport category: 3, max. ADR 1.1.3.6. 1000 L - Limited quantities: 5 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4 <p><u>Transport by sea (IMDG 39-18):</u></p> <ul style="list-style-type: none"> - Class: 3 - Packing group: III - Emergency Sheet (EmS): F-E,S_E - First Aid Guide (MFAG): 310,313 - Marine pollutant: No. - Transport document: Shipping Bill of lading. <p><u>Transport by air (ICAO/IATA 2021):</u></p> <ul style="list-style-type: none"> - Class: 3 - Packing group: III - Transport document: Air Bill of lading. <p><u>Transport by inland waterways (ADN):</u> Not available.</p> </div> <div style="width: 35%; text-align: right;"> <p>FP<23°C, viscous according 2.2.3.1.4. <450 L (ADR) or 2.3.2.2. <30 L (IMDG) or 3.3.3.1.1. <30 L (IATA), VP>175 kPa50°C</p> <div style="display: flex; flex-direction: column; align-items: center;">    </div> </div> </div>	
14.4	<u>PACKING GROUP:</u> See section 14.3	
14.5	<u>ENVIRONMENTAL HAZARDS:</u> Not applicable (not classified as hazardous for the environment).	
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.	
14.7	<u>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</u> Not applicable.	
SECTION 15 : REGULATORY INFORMATION		
15.1	<p><u>EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:</u> The regulations applicable to this product generally are listed throughout this Safety Data Sheet.</p> <p><u>Restrictions on manufacture, placing on market and use:</u> See section 1.2</p> <p><u>Tactile warning of danger:</u> Not applicable (product for professional or industrial use).</p> <p><u>Child safety protection:</u> Not applicable (the classification criteria are not met).</p> <p><u>OTHER REGULATIONS:</u></p> <p><u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2</p> <p><u>Other local legislations:</u> The receiver should verify the possible existence of local regulations applicable to the chemical.</p>	
15.2	<u>CHEMICAL SAFETY ASSESSMENT:</u> A chemical safety assessment has not been carried out for this mixture.	



QUICK WHEEL SILVER 1000ML
Code: 5004-001136



SECTION 16 : OTHER INFORMATION

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:Hazard statements according the Regulation (EU) No. 1272/2008~2020/1182 (CLP), Annex III:

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H228 Flammable solid. H261 In contact with water releases flammable gases. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H360D May damage the unborn child. H373iE May cause damage to hearing organs through prolonged or repeated exposure if inhaled.

Notes related to the identification, classification and labelling of the substances:

Note H : The classification and label shown for this substance applies to the dangerous property(ies) indicated by the risk phrase(s) in combination with the category(ies) of danger shown.

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1% w/w benzene (EC No. 200-753-7).

Note T : This substance may be marketed in a form which does not have the physico-chemical properties as indicated by the classification in the Annex I entry.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency : ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2018).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

HISTORIC:

Version: 1

Date of compilation:

30/12/2021

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.