

## SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 05/08/2022 Page 1 / 12

	<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223	 
--	--	---



Version: 1 Date of compilation: 05/08/2022

Date of printing: 05/08/2022

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**



1.1	<b>PRODUCT IDENTIFIER:</b> UFI: 109G-D34R-F006-HPXD	<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223
1.2	<b>RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:</b> <u>Intended uses (main technical functions):</u> [X] Industrial [X] Professional [ ] Consumers Catalyst. <u>Relevant product types:</u> Paints and varnishes, industrial, professional. <u>Sectors of use:</u> Industrial manufacturing (SU3). Professional uses (SU22). <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as 'Intended or identified uses'. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.	
1.3	<b>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:</b> <b>CAR REPAIR SYSTEM S.A.</b> Pol. Ind. 2 de Octubre. C/ Jose Muñoz, 6 - E-18320 - Santa Fe - Granada (Española) Phone: +34 95 8431792 <u>E-mail address of the person responsible for the Safety Data Sheet:</u> info@carrepairsystem.eu	
1.4	<b>EMERGENCY TELEPHONE NUMBER:</b> +34 95 8431792 (L-J 8:30-14 / 15-18 h. V 8:30-14:30 h.) (working hours)	









**SECTION 2 : HAZARDS IDENTIFICATION**

2.1	<b>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:</b> Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP):</u> WARNING: Flam. Liq. 3:H226   Skin Sens. 1:H317   STOT SE (irrit.) 3:H335   STOT SE (narcosis) 3:H336   Aquatic Chronic 3:H412   EUH066					
	<b>Danger class</b>	<b>Classification of the mixture</b>	<b>Cat.</b>	<b>Routes of exposure</b>	<b>Target organs</b>	<b>Effects</b>
	<u>Physicochemical:</u> 	Flam. Liq. 3:H226 Skin Sens. 1:H317 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336	a) Cat.3 c) Cat.1 c) Cat.3 c) Cat.3	- Skin Inhalation Inhalation	- Skin Respiratory tract CNS	- Allergy Irritation Narcosis
	<u>Human health:</u> 	Aquatic Chronic 3:H412 EUH066	c) Cat.3 c) -	- Skin	- Skin	- Dryness, Cracking
	<u>Environment:</u>					

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2	<b>LABEL ELEMENTS:</b>  		This product is labelled with the signal word WARNING in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP)		
	<b>Hazard statements:</b> H226 H335 H336 H317 H412 EUH066	Flammable liquid and vapour. May cause respiratory irritation. May cause drowsiness or dizziness. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.			
	<b>Precautionary statements:</b> P102 P210 P280F	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection.			

		<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223		 	
		P363 P303+P361+P353-P352-P312 P273-P501a EUH204 <u>Supplementary statements:</u> <u>Substances that contribute to classification:</u> n-butyl acetate HDI oligomers, isocyanurate Hydrocarbons C9 aromatics		Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash with plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell. Avoid release to the environment. Dispose of contents/container in accordance with local regulations.  Contains isocyanates. May produce an allergic reaction.	
2.3		<u>OTHER HAZARDS:</u> Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: <u>Other physicochemical hazards:</u> Vapours may form with air a mixture potentially flammable or explosive. <u>Other adverse human health effects:</u> People with hypersensitive respiratory tract (by instance, asthma or chronic bronchitis) should not handle this product. The symptoms in the respiratory tract may appear even last few hours of excessive exposure. The major dangers for respiratory ways are the dust, vapours or aerosols. <u>Other negative environmental effects:</u> Does not contain substances that fulfil the PBT/vPvB criteria.			
SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS					
3.1		<u>SUBSTANCES:</u> Not applicable (mixture).			
3.2		<u>MIXTURES:</u> This product is a mixture. <u>Chemical description:</u> HARDENER.  <u>INGREDIENTS:</u>			
		<div>40 &lt; 50 % </div> <div><b>n-butyl acetate</b> CAS: 123-86-4 , EC: 204-658-1 CLP: Warning: Flam. Liq. 3:H226   STOT SE (narcosis) 3:H336   EUH066 REACH: 01-2119485493-29 Index No. 607-025-00-1 &lt; REACH / ATP01</div>			
		<div>40 &lt; 50 % </div> <div><b>HDI oligomers, isocyanurate</b> (CAS: 28182-81-2) , List No. 931-274-8 CLP: Warning: Acute Tox. (inh.) 4:H332   Skin Sens. 1:H317   STOT SE (irrit.) 3:H335 REACH: 01-2119485796-17 Autoclassified &lt; REACH</div>			
		<div>5 &lt; 10 % </div> <div><b>Hydrocarbons C9 aromatics</b> (CAS: 64742-95-6) , List No. 918-668-5 CLP: Danger: Flam. Liq. 3:H226   STOT SE (irrit.) 3:H335   STOT SE (narcosis) 3:H336   Asp. Tox. 1:H304   Aquatic Chronic 2:H411   EUH066 Autoclassified &lt; REACH</div>			
		<div>1 &lt; 3 % </div> <div><b>Xylene (mixture of isomers)</b> CAS: 1330-20-7 , EC: 215-535-7 CLP: Danger: Flam. Liq. 3:H226   Acute Tox. (inh.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOT RE 2:H373   Asp. Tox. 1:H304   Aquatic Chronic 3:H412 REACH: 01-2119488216-32 Autoclassified &lt; REACH</div>			
		<div>&lt; 0,15 % </div> <div><b>2,6-di-tert-butyl-p-cresol</b> CAS: 128-37-0 , EC: 204-881-4 CLP: Warning: Aquatic Chronic 1:H410 (M=1) REACH: 01-2119555270-46 Autoclassified &lt; REACH</div>			
		<u>Impurities:</u> Does not contain other components or impurities which will influence the classification of the product.			
		<u>Stabilizers:</u> None			
		<u>Reference to other sections:</u> For more information on hazardous ingredients, see sections 8, 11, 12 and 16.			
		<u>SUBSTANCES OF VERY HIGH CONCERN (SVHC):</u> List updated by ECHA on 08/07/2021. <u>Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:</u> None <u>Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:</u> None			
		<u>PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:</u> Does not contain substances that fulfil the PBT/vPvB criteria.			



**EASY FILLER EXTRA FAST HARDENE**  
Code: 5009-001223



#### SECTION 4 : FIRST AID MEASURES

##### 4.1 DESCRIPTION OF FIRST-AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
<u>Inhalation:</u> 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
<u>Skin:</u> 	Skin contact causes redness. Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners. In the case of skin reddening or rashes, contact a doctor immediately.
<u>Eyes:</u>	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
<u>Ingestion:</u>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

##### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

##### 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.  
Antidotes and contraindications: Specific antidote not known.

#### SECTION 5 : FIRE-FIGHTING MEASURES

##### 5.1 EXTINGUISHING MEDIA:

Extinguishing powder or CO<sub>2</sub>. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

##### 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, nitrogen oxides, isocyanate vapours, traces of hydrocyanic acid. Exposure to combustion or decomposition products may be a hazard to health.

##### 5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.  
Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.




#### SECTION 6 : ACCIDENTAL RELEASE MEASURES

##### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

##### 6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

	<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223	 
6.3	<b><u>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</u></b> Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises: water, ethanol or isopropanol and concentrated ammonia solution (d=0,880) = 45/50/5 parts by volume. Another possible (non-flammable) decontaminant is made up of water and sodium carbonate = 95/5 parts by weight. Add the same decontaminant to any residues and allow to stand for several days in an un-sealed container until no further reaction occurs. Keep the remains in a closed container.	
6.4	<b><u>REFERENCE TO OTHER SECTIONS:</u></b> For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For waste disposal, follow the recommendations in section 13.	
<b>SECTION 7 : HANDLING AND STORAGE</b>		
7.1	<b><u>PRECAUTIONS FOR SAFE HANDLING:</u></b> Comply with the existing legislation on health and safety at work. <b><u>General recommendations:</u></b> Avoid any type of leakage or escape. Keep the container tightly closed. <b><u>Recommendations for the prevention of fire and explosion risks:</u></b> Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used. - Flash point : 23. °C - Autoignition temperature : 415. °C - Lower/upper flammability or explosive limits : 1.4* - 7.4* % Volume 25°C <b><u>Recommendations for the prevention of toxicological risks:</u></b> People with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which isocyanate containing products are used. Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8. <b><u>Recommendations for the prevention of environmental contamination:</u></b> Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.	
7.2	<b><u>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u></b> Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. Precautions should be taken to minimise exposure to atmospheric humidity or water, as carbon dioxide may be formed which, in closed containers can result in pressurisation. Care should be taken when re-opening partly used containers. Due to the sensitivity to humidity of the isocyanates, this product should be kept in the original container, or under pressure of dried nitrogen, for example. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10. <b><u>Class of storage</u></b> : According to current legislation. <b><u>Maximum storage period</u></b> : 6. months <b><u>Temperature interval</u></b> : min: 5. °C, max: 20. °C (recommended). <b><u>Incompatible materials:</u></b> Keep away from water, oxidizing agents, acids, alkalis, amines, alcohols, peroxides. Clean the application equipment with a compatible solvent. Never leave the equipment filled with the cleaning solvent for prolonged periods, especially when used for cleaning solvents recovered which may contain moisture or alcohols, to prevent the product from hardening in the equipment, causing seals on the hoses or guns. <b><u>Type of packaging:</u></b> According to current legislation. <b><u>Limit quantity (Seveso III): Directive 2012/18/EU:</u></b> - Named dangerous substances/mixtures: None - Hazard categories and lower-/upperthreshold quantities in tonnes (t): · Physical hazards: Flammable liquid and vapour (P5c) (5000t/50000t). · Health hazards: Not applicable · Environmental hazards: Not applicable · Other hazards: Not applicable. - Threshold quantity for the application of lower-tier requirements: 5000 tons - Threshold quantity for the application of upper-tier requirements: 50000 tons - Remarks: The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.	
7.3	<b><u>SPECIFIC END USES:</u></b> For the use of this product particular recommendations apart from that already indicated are not available.	



EASY FILLER EXTRA FAST HARDENE  
Code: 5009-001223

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 CONTROL PARAMETERS:**

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2020	Year	TLV-TWA ppm	mg/m <sup>3</sup>	TLV-STEL ppm	mg/m <sup>3</sup>	Remarks
n-butyl acetate	2015	50.	237.	150.	713.	Recommended A4 , BEI IFV A4
Hydrocarbons C9 aromatics		50.	290.	-	-	
Xylene	1996	100.	434.	150.	651.	
2,6-di-tert-butyl-p-cresol	2001	-	2.0	-	-	

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

A4 - Non classified as carcinogenic in humans.

IFV - Inhalable fraction and vapour.

BEI - Biological exposure index (biological monitoring).

Inhalable fraction and vapour (IFV): IFV notation indicates those chemical agents that may occur in the workplace, both as particulate matter and as vapour, so that the two phases can coexist, both contributing to exposure. This situation can occur mainly in the following cases: a) When the agent in question has an 'intermediate' value of the vapour pressure (in these cases it is taking into account the relationship between its concentration in air saturated vapour and the value of TWA, and the note is assigned, generally, when the ratio between the two quantities is between 0.1 and 10), b) Because of the form of use of the chemical agent (e.g. spraying), c) In the processes involving large temperature changes that may affect the physical state of the chemical agent, and d) In the processes in which a significant fraction of vapour can be dissolved or adsorbed onto particles of other substances, like what happens with water soluble agents in high humidity environments. For more information, see C.Perez and S.C.Soderholm. Some chemicals requiring special consideration when deciding whether to sample the particle, vapor or both phases of an atmosphere. Appl. Occup. Environ. Hyg. 6 (10), 859-864. 1991).

BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

- Xylenes (technical or commercial grade) (2011): Biological determinant: methylhippuric acids in urine, BEI: 1.5 g/g creatinine, Sampling time: end of shift (2).

(2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases.

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers:

- Systemic effects, acute and chronic:

	DNEL Inhalation mg/m <sup>3</sup>	DNEL Cutaneous mg/kg bw/d	DNEL Oral mg/kg bw/d
n-butyl acetate	960. (a) 480. (c)	11.0 (a) 11.0 (c)	- (a) - (c)
HDI oligomers, isocyanurate	s/r (a) s/r (c)	s/r (a) s/r (c)	- (a) - (c)
Xylene (mixture of isomers)	289. (a) 77.0 (c)	s/r (a) 180. (c)	- (a) - (c)
2,6-di-tert-butyl-p-cresol	- (a) 1.76 (c)	s/r (a) 0.500 (c)	- (a) - (c)

Derived no-effect level, workers:

- Local effects, acute and chronic:

	DNEL Inhalation mg/m <sup>3</sup>	DNEL Cutaneous mg/cm <sup>2</sup>	DNEL Eyes mg/cm <sup>2</sup>
n-butyl acetate	960. (a) 480. (c)	s/r (a) s/r (c)	s/r (a) - (c)
HDI oligomers, isocyanurate	1.00 (a) 0.500 (c)	a/r (a) a/r (c)	s/r (a) - (c)
Xylene (mixture of isomers)	289. (a) s/r (c)	s/r (a) s/r (c)	- (a) - (c)
2,6-di-tert-butyl-p-cresol	- (a) - (c)	s/r (a) s/r (c)	s/r (a) - (c)

Derived no-effect level, general population:


















Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

a/r - DNEL not derived (high hazard).

		EASY FILLER EXTRA FAST HARDENE Code: 5009-001223		 															
<u>PREDICTED NO-EFFECT CONCENTRATION (PNEC):</u>																			
<u>Predicted no-effect concentration, aquatic organisms:</u> - Fresh water, marine water and intermittent release: n-butyl acetate HDI oligomers, isocyanurate Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<u>PNEC Fresh water</u> mg/l  0.180 0.127 0.327 0.000200	<u>PNEC Marine</u> mg/l  0.0180 0.0127 0.327 0.000020	<u>PNEC Intermittent</u> mg/l  0.360 1.27 0.327 0.00200															
<u>- Wastewater treatment plants (STP) and sediments in fresh- and marine water:</u> n-butyl acetate HDI oligomers, isocyanurate Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<u>PNEC STP</u> mg/l  35.6 38.3 6.58 0.0170	<u>PNEC Sediments</u> mg/kg dw/d  0.981 266700. 12.5 0.458	<u>PNEC Sediments</u> mg/kg dw/d  0.0981 26670. 12.5 0.0458															
<u>Predicted no-effect concentration, terrestrial organisms:</u> - Air, soil and effects for predators and humans: n-butyl acetate HDI oligomers, isocyanurate Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<u>PNEC Air</u> mg/m3  s/r s/r - s/r	<u>PNEC Soil</u> mg/kg dw/d  0.0903 53182. 2.31 0.0539	<u>PNEC Oral</u> mg/kg dw/d  n/b n/b - 16.7															
(-) - PNEC not available (without data of registration REACH). s/r - PNEC not derived (not identified hazard). n/b - PNEC not derived (not bioaccumulative potential).																			
8.2	<u>EXPOSURE CONTROLS:</u>  <u>ENGINEERING MEASURES:</u>  <div></div> <p>Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.</p> <p><u>Protection of respiratory system:</u> Avoid the inhalation of vapours. <u>Protection of eyes and face:</u> It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area. <u>Protection of hands and skin:</u> It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.</p> <p><u>OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425:</u> As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.</p> <table><tr><td><u>Mask:</u> </td><td>In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. If the working area is insufficiently ventilated, or when operators, whether spraying or not, are inside the spraybooth, compressed air-fed respiratory protective equipment (EN137) is required. For short periods of work, you can consider the utilisation of a combination mask with gas and particle filters, type A2-P2 (EN14387/EN143).</td></tr><tr><td><u>Safety goggles:</u> </td><td>Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.</td></tr><tr><td><u>Face shield:</u></td><td>No.</td></tr><tr><td><u>Gloves:</u> </td><td>Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of &gt;240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time &gt;30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.</td></tr><tr><td><u>Boots:</u></td><td>No.</td></tr><tr><td><u>Apron:</u></td><td>No.</td></tr><tr><td><u>Clothing:</u></td><td>Advisable.</td></tr></table>					<u>Mask:</u> 	In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. If the working area is insufficiently ventilated, or when operators, whether spraying or not, are inside the spraybooth, compressed air-fed respiratory protective equipment (EN137) is required. For short periods of work, you can consider the utilisation of a combination mask with gas and particle filters, type A2-P2 (EN14387/EN143).	<u>Safety goggles:</u> 	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.	<u>Face shield:</u>	No.	<u>Gloves:</u> 	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.	<u>Boots:</u>	No.	<u>Apron:</u>	No.	<u>Clothing:</u>	Advisable.
<u>Mask:</u> 	In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. If the working area is insufficiently ventilated, or when operators, whether spraying or not, are inside the spraybooth, compressed air-fed respiratory protective equipment (EN137) is required. For short periods of work, you can consider the utilisation of a combination mask with gas and particle filters, type A2-P2 (EN14387/EN143).																		
<u>Safety goggles:</u> 	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.																		
<u>Face shield:</u>	No.																		
<u>Gloves:</u> 	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.																		
<u>Boots:</u>	No.																		
<u>Apron:</u>	No.																		
<u>Clothing:</u>	Advisable.																		



**SAFETY DATA SHEET (REACH)**

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 05/08/2022 Page 7 / 12


**EASY FILLER EXTRA FAST HARDENE**  
 Code: 5009-001223
**Thermal hazards:**

Not applicable (the product is handled at room temperature).

**ENVIRONMENTAL EXPOSURE CONTROLS:**

Avoid any spillage in the environment. Avoid any release into the atmosphere.

**Spills on the soil:** Prevent contamination of soil.**Spills in water:** Do not allow to escape into drains, sewers or water courses.- **Water Management Act:** This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.**Emissions to the atmosphere:** Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

- **VOC (industrial installations):** If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents : 55.3% Weight , VOC (supply) : 55.3% Weight , VOC : 37.1% C (expressed as carbon) , Molecular weight (average) : 116.7 , Number C atoms (average) : 6.5.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:****Appearance**

- Physical state : Liquid.
- Colour : Colourless.
- Odour : Characteristic.

**pH-value**

- pH : Not applicable (non-aqueous media).

**Change of state**

- Melting point : -54. °C
- Boiling interval : 127. - 140\* °C at 760 mmHg

**Density**

- Vapour density : 4\* at 20°C 1 atm. Relative air
- Relative density : 0.988 at 20/4°C Relative water

**Stability****Viscosity:**

- Dynamic viscosity : 60. cps 20°C
- Kinematic viscosity : 21. mm<sup>2</sup>/s at 40°C

**Volatility:**

- Vapour pressure : 15. hPa at 20°C
- Vapour pressure : 5.2\* kPa at 50°C

**Solubility(ies)**

- Solubility in water : Not applicable
- Partition coefficient: n-octanol/water : Not applicable (mixture).

**Flammability:**

- Flash point : 23. °C
- Lower/upper flammability or explosive limits : 1.4\* - 7.4\* % Volume 25°C
- Autoignition temperature : 415. °C

**Explosive properties:**

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

**Oxidizing properties:**

Not classified as oxidizing product.

\*Estimated values based on the substances composing the mixture.

**9.2 OTHER INFORMATION:**

- Heat of combustion : 6039\* Kcal/kg
- Solids : 44.7 % Weight
- VOC (supply) : 55.3 % Weight
- VOC (supply) : 550.3 g/l

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

**SECTION 10 : STABILITY AND REACTIVITY****10.1 REACTIVITY:****Corrosivity to metals:** It is not corrosive to metals.**Pyrophorical properties:** It is not pyrophoric.**10.2 CHEMICAL STABILITY:**

Stable under recommended storage and handling conditions.

**10.3 POSSIBILITY OF HAZARDOUS REACTIONS:**Possible dangerous reaction with water, oxidizing agents, acids, alkalis, amines, alcohols, peroxides. Exothermic reaction with amines and alcohols. Reacts with water under evolution of CO<sub>2</sub>.

## SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 05/08/2022 Page 8 / 12

	<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223	 
--	--	---

- 10.4 **CONDITIONS TO AVOID:**  
 - **Heat:** Keep away from sources of heat.  
 - **Light:** If possible, avoid direct contact with sunlight.  
 - **Air:** The product is not affected by exposure to air, but should not be left the containers open.  
 - **Humidity:** Avoid humidity. Precautions should be taken to minimise exposure to atmospheric humidity or water, as carbon dioxide may be formed which, in closed containers can result in pressurisation.  
 - **Pressure:** Not relevant.  
 - **Shock:** The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.
- 10.5 **INCOMPATIBLE MATERIALS:**  
 Keep away from water, oxidizing agents, acids, alkalis, amines, alcohols, peroxides. Clean the application equipment with a compatible solvent. Never leave the equipment filled with the cleaning solvent for prolonged periods, especially when used for cleaning solvents recovered which may contain moisture or alcohols, to prevent the product from hardening in the equipment, causing seals on the hoses or guns.
- 10.6 **HAZARDOUS DECOMPOSITION PRODUCTS:**  
 As consequence of thermal decomposition, hazardous products may be produced, including isocyanates.

**SECTION 11 : TOXICOLOGICAL INFORMATION**

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

11.1 **INFORMATION ON TOXICOLOGICAL EFFECTS:****ACUTE TOXICITY:****Dose and lethal concentrations for individual ingredients :**

	<b>LD50 (OECD 401)</b> mg/kg bw oral	<b>LD50 (OECD 402)</b> mg/kg bw cutaneous	<b>LC50 (OECD 403)</b> mg/m <sup>3</sup> -4h inhalation
n-butyl acetate	10768. Rat	17600. Rabbit	> 23400. Rat
HDI oligomers, isocyanurate	2500. Rat	> 2000. Rat	> 390. Rat
Hydrocarbons C9 aromatics	3592. Rat	3160. Rabbit	> 6193. Rat
Xylene (mixture of isomers)	4300. Rat	1700. Rabbit	> 22080. Rat
2,6-di-tert-butyl-p-cresol	6000. Rat	> 2000. Rat	

**Estimates of acute toxicity (ATE) for individual ingredients :**

	<b>ATE</b> mg/kg bw oral	<b>ATE</b> mg/kg bw cutaneous	<b>ATE</b> mg/m <sup>3</sup> -4h inhalation
HDI oligomers, isocyanurate	-	-	20000.* Vapours
Xylene (mixture of isomers)	-	1100.*	11000.* Vapours

(\*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

**No observed adverse effect level**

Not available

**Lowest observed adverse effect level**

Not available

**INFORMATION ON LIKELY ROUTES OF EXPOSURE: Acute toxicity:**

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
<b>Inhalation:</b> Not classified	ATE > 20000 mg/m <sup>3</sup>	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<b>Skin:</b> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<b>Eyes:</b> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
<b>Ingestion:</b> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).





**EASY FILLER EXTRA FAST HARDENE**  
Code: 5009-001223



#### CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Respiratory corrosion/irritation:</u> 	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 1.2.6. 3.8.3.4.
<u>Skin corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
<u>Serious eye damage/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
<u>Skin sensitisation:</u> 	Skin 	Cat.1	SENSITISING: May cause an allergic skin reaction.	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

#### ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Aspiration hazard:</u> Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

#### SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Respiratory:</u> 	SE	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 3.8.3.4.
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

#### CMR EFFECTS:

Carcinogenic effects: It is not considered as a carcinogenic product.

Genotoxicity: It is not considered as a mutagenic product.

Toxicity for reproduction: Does not harm fertility. Does not harm the unborn child.

Effects via lactation: Not classified as a hazardous product for children breast-fed.

#### DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat and other effects may be the same as described in the exposure to vapours.

Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated exposure may cause skin dryness or cracking.




#### INTERACTIVE EFFECTS:

Not available.

#### INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption: Not available.




Basic toxicokinetics: Not available.




	EASY FILLER EXTRA FAST HARDENE Code: 5009-001223			 	
<b>ADDITIONAL INFORMATION:</b> Based on the properties of the isocyanate content of this product and existing technical data of similar preparations, it can be concluded that respiratory exposure may cause acute irritation and/or sensitization of the respiratory system, resulting in asthmatic symptoms, wheezing and a tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to airborne concentrations of isocyanates well below the occupational exposure limit. Repeated exposure may lead to permanent respiratory disability. In case of prolonged contact, the skin can dry up and irritation could appear.					
SECTION 12 : ECOLOGICAL INFORMATION					
No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).					
12.1	<b>TOXICITY:</b>				
<b>Acute toxicity in aquatic environment for individual ingredients :</b> n-butyl acetate HDI oligomers, isocyanurate Hydrocarbons C9 aromatics Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<b>LC50 (OECD 203)</b> mg/l-96hours > 18. Fishes > 100. Fishes > 9.2 Fishes > 13. Fishes 0.20 Fishes	<b>EC50 (OECD 202)</b> mg/l-48hours > 44. Daphnia > 100. Daphnia > 3.2 Daphnia > 16. Daphnia 0.48 Daphnia	<b>EC50 (OECD 201)</b> mg/l-72hours 675. Algae > 1000. Algae > 2.9 Algae > 10. Algae 0.42 Algae	
<b>No observed effect concentration</b> n-butyl acetate		<b>NOEC (OECD 210)</b> mg/l-28days	<b>NOEC (OECD 211)</b> mg/l-21days 23. Daphnia	<b>NOEC (OECD 201)</b> mg/l-72hours	
<b>Lowest observed effect concentration</b> Not available					
<b>ASSESSMENT OF AQUATIC TOXICITY:</b>					
<b>Aquatic toxicity</b>		<b>Cat.</b>	<b>Main hazards to the aquatic environment</b>		<b>Criteria</b>
<b>Acute aquatic toxicity:</b> Not classified		-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).		GHS/CLP 4.1.3.5.5.3.
<b>Chronic aquatic toxicity:</b>		Cat.3	HARMFUL: Harmful to aquatic life with long lasting effects.		GHS/CLP 4.1.3.5.5.4.
CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components. CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.					
12.2	<b>PERSISTENCE AND DEGRADABILITY:</b> Not available.				
<b>Aerobic biodegradation for individual ingredients :</b> n-butyl acetate HDI oligomers, isocyanurate Hydrocarbons C9 aromatics Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<b>DOO</b> mgO2/g 2204.  3195. 2620. 2977.	<b>%DBO/DOO</b> 5 days 14 days 28 days ~ 80. ~ 82. ~ 83. 1. ~ 52. ~ 81. ~ 88.	<b>Biodegradability</b> Easy Not easy Easy Easy Not easy	
Note: Biodegradability data correspond to an average of data from various bibliographic sources.					
12.3	<b>BIOACCUMULATIVE POTENTIAL:</b> Not available.				
<b>Bioaccumulation for individual ingredients :</b> n-butyl acetate HDI oligomers, isocyanurate Hydrocarbons C9 aromatics Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<b>log Pow</b> 1.81 5.54 3.30 3.16 4.17	<b>BCF</b> L/kg 6.9 (calculated) 3.2 (calculated) 70. (calculated) 56. (calculated) 646. (calculated)	<b>Potential</b> Not bioaccumulative. Not bioaccumulative. Low Low High	
12.4	<b>MOBILITY IN SOIL:</b> Not available.				
<b>Mobility for individual ingredients :</b> n-butyl acetate HDI oligomers, isocyanurate Hydrocarbons C9 aromatics Xylene (mixture of isomers) 2,6-di-tert-butyl-p-cresol		<b>log Poc</b> 1.84 5.15 2.96 2.25 3.91	<b>Constant of Henry</b> Pa·m3/mol 20°C 28. (calculated) 0.00000 (calculated) 440. (calculated) 660. (calculated)	<b>Potential</b> Not bioaccumulative. Not bioaccumulative. Low Low High	

**SAFETY DATA SHEET (REACH)**

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Date of compilation: 05/08/2022 Page 11 / 12

	<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223	 
12.5	<b>RESULTS OF PBT AND VPVB ASSESMENT:</b> <a href="#">Annex XIII of Regulation (EC) no. 1907/2006:</a> Does not contain substances that fulfil the PBT/vPvB criteria.	
12.6	<b>OTHER ADVERSE EFFECTS:</b> <a href="#">Ozone depletion potential:</a> Not available. <a href="#">Photochemical ozone creation potential:</a> Not available. <a href="#">Earth global warming potential:</a> In case of fire or incineration liberates CO2. <a href="#">Endocrine disrupting potential:</a> Not available.	
<b>SECTION 13 : DISPOSAL CONSIDERATIONS</b>		
13.1	<b>WASTE TREATMENT METHODS:</b> <a href="#">Directive 2008/98/EC~Regulation (EU) no. 1357/2014:</a> Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.  <a href="#">Disposal of empty containers:</a> <a href="#">Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:</a> Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.  <a href="#">Procedures for neutralising or destroying the product:</a> Controlled incineration in special facilities for chemical waste, in accordance with local regulations.	
<b>SECTION 14 : TRANSPORT INFORMATION</b>		
14.1	<b>UN NUMBER:</b> 1263	
14.2	<b>UN PROPER SHIPPING NAME:</b> PAINT	
14.3	<b>TRANSPORT HAZARD CLASS(ES):</b>  <a href="#">Transport by road (ADR 2021) and Transport by rail (RID 2021):</a>  - Class: 3 - Packing group: III - Classification code: F1 - Tunnel restriction code: (D/E) - Transport category: 3, max. ADR 1.1.3.6. 1000 L - Limited quantities: 5 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4  <a href="#">Transport by sea (IMDG 39-18):</a>  - Class: 3 - Packing group: III - Emergency Sheet (EmS): F-E,S_E - First Aid Guide (MFAG): 310,313 - Marine pollutant: No. - Transport document: Shipping Bill of lading.  <a href="#">Transport by air (ICAO/IATA 2021):</a>  - Class: 3 - Packing group: III - Transport document: Air Bill of lading.  <a href="#">Transport by inland waterways (ADN):</a> Not available.	
14.4	<b>PACKING GROUP:</b> See section 14.3	
14.5	<b>ENVIRONMENTAL HAZARDS:</b> Not applicable.	
14.6	<b>SPECIAL PRECAUTIONS FOR USER:</b> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.	
14.7	<b>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</b> Not applicable.	
<b>SECTION 15 : REGULATORY INFORMATION</b>		
15.1	<b>EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:</b> The regulations applicable to this product generally are listed throughout this Safety Data Sheet.	

	<b>EASY FILLER EXTRA FAST HARDENE</b> Code: 5009-001223	 
	<p><u>Restrictions on manufacture, placing on market and use:</u> See section 1.2</p> <p><u>Tactile warning of danger:</u> Not applicable (the classification criteria are not met).</p> <p><u>Child safety protection:</u> Not applicable (the classification criteria are not met).</p> <p><u>OTHER REGULATIONS:</u></p> <p><u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2</p> <p><u>Other local legislations:</u> The receiver should verify the possible existence of local regulations applicable to the chemical.</p>	
15.2	<p><u>CHEMICAL SAFETY ASSESSMENT:</u> A chemical safety assessment has not been carried out for this mixture.</p>	
<b>SECTION 16 : OTHER INFORMATION</b>		
	<p><u>TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:</u>  <u>Hazard statements according the Regulation (EU) No. 1272/2008~2020/1182 (CLP), Annex III:</u>            H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H373iE May cause damage to hearing organs through prolonged or repeated exposure if inhaled.</p> <p><u>Indications for preparations containing isocyanates:</u>            Ready-to-use preparations containing isocyanates may have an irritant effect on mucous membranes -especially on breathing organs- and cause hypersensitivity reactions. Inhalation of vapour or spray mist may cause sensitisation. When handling preparations containing isocyanates all precautions required for solvent-containing preparations must be followed. Vapour and spray mist in particular should not be inhaled. Allergics and asthmatics, as well as people prone to respiratory ailments should not work with isocyanate-containing preparations.</p> <p><u>EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:</u> See sections 9.1, 11.1 and 12.1.</p> <p><u>ADVISES ON ANY TRAINING APPROPRIATE FOR WORKERS:</u>            It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.</p> <p><u>MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:</u></p> <ul style="list-style-type: none"> <li>European Chemicals Agency : ECHA, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a></li> <li>Access to European Union Law, <a href="http://eur-lex.europa.eu/">http://eur-lex.europa.eu/</a></li> <li>Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).</li> <li>Threshold Limit Values, (AGCIH, 2018).</li> <li>Riesgos y Patología por Isocianatos, G.Alomar (INSHT, DT.54.89, 1989).</li> <li>ISOPA directives for the safety in the load/unload, transport and storage of TDI and MDI. ISOPA publication number: PSC-0014-GUIDL-EN.</li> <li>European agreement on the international carriage of dangerous goods by road, (ADR 2021).</li> <li>International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).</li> </ul> <p><u>ABBREVIATIONS AND ACRONYMS:</u>            List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:</p> <ul style="list-style-type: none"> <li>REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.</li> <li>GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.</li> <li>CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.</li> <li>EINECS: European Inventory of Existing Commercial Chemical Substances.</li> <li>ELINCS: European List of Notified Chemical Substances.</li> <li>CAS: Chemical Abstracts Service (Division of the American Chemical Society).</li> <li>UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.</li> <li>SVHC: Substances of Very High Concern.</li> <li>PBT: Persistent, bioaccumulable and toxic substances.</li> <li>vPvB: Very persistent and very bioaccumulable substances.</li> <li>VOC: Volatile Organic Compounds.</li> <li>DNEL: Derived No-Effect Level (REACH).</li> <li>PNEC: Predicted No-Effect Concentration (REACH).</li> <li>LD50: Lethal dose, 50 percent.</li> <li>LC50: Lethal concentration, 50 percent.</li> <li>UN: United Nations Organisation.</li> <li>ADR: European agreement concerning the international carriage of dangerous goods by road.</li> </ul> <p><u>SAFETY DATA SHEET REGULATIONS:</u>            Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.</p> <p><u>HISTORIC:</u>                      <u>Date of compilation:</u>            Version: 1                      05/08/2022</p>	

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.