



EN

TECHNICAL DATA SHEET

DESCRIPTION

Plastic Adhesion Promoter based on a solution of special additives that provide adhesion on PP(EPDM).

APPLICATION

Suitable as adhesion promoter in spray painting systems. Its power as an adhesion promoter on various surfaces makes it ideal in plastic painting.

INSTRUCTIONS FOR USE

- Shake the aerosol very well before use, about one minute after hearing the noise of the mixer.
- Apply to clean, degreased, dry surfaces free of mould release agents.
- Apply in thin layers for best results. Apply 1-2 coats of the product.
- Invert the aerosol to purge the valve after use.
- Do not apply to connected equipment and use in well-ventilated areas.
- Request safety data sheets.

FEATURES

- Very fast Drying, after 10 minutes
- Ease of application and repainting
- Excellent adhesion on polypropylene (modified with EPDM). On other plastics it is advisable to test before use.

- **Physical properties**

Colour	Colourless		
Total Dryness	10'		
Dry Film Thickness	4µm/ layer		
Theoretical Yield	2m ²		
Thinner	Ethyl acetate		
Product Life	> 2 years		
Recoat	After 10'		
Application Conditions	Min. Amb. Temp.: 8°C	Surface Temp.: 5-50°C	Max. Humidity: 85% R.H.P.

- **Packaging characteristics**

Nominal capacity	400ml
Container heat resistance	10'
Propellant	BP

SAFETY REGULATIONS

See Safety Data Sheet.

AVAILABLE PRODUCTS

Code	Description	Size
2006-002590	QUICK PLASTIC PRIMER	400ml

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee the perfect quality of the product. However, considering that the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.