



DESCRIPTION

Seam sealer tape for exchanging panels (doors, bonnets, boots) for cars, trucks, boats, vans, etc. It is fast and offers an excellent finish, the door seal looks like new.

APPLICATION

- Recommended working temperature: 10/20 ° C.
- Completely removes previous sealant, silicone, oil, dust, etc.
- Apply the aerosol primer for sealing tape in two passes. Allow to dry for 5 minutes (be sure to use this primer for better adhesion and to prevent corrosion).
- Apply the tape to the desired locations slowly.
- Use the roller to pressurise the tape (as needed).
- To fit the corners correctly, cut the tape at a 45° angle.
- Prior application of primer on the tape is necessary.

STORAGE AND SHELF LIFE

12 months in a cool and dry place in its original packaging (+ 5 ° C to + 25 ° C)

AVAILABLE PACKAGING

Code	Description	Size
2008-056250	Seam Sealer	8mm x 16m
2008-056260	Seam Sealer	10mm x 16m
2008-056270	Seam Sealer	20mm x 1mm x 5m
2008-056280	Seam Sealer Convex Tape	8mm x 9m
2008-056285	Seam Sealer Convex Tape	10mm x 9m
2008-056275	Seam Sealer Convex Tape	3mm x 6.5m
2008-056295	Seam Sealer tape roller	
2008-056296	Seam Sealer bevelled tape roller	

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.