



DESCRIPTION

Highly elastic multifunctional putty specially designed for application on plastic substrates, including polypropylene. Easy application and modeling. Can be used as a filler and as a fine putty. Provides an unsanded, easy-to-sand coating. It also adheres to metal substrates such as steel, galvanized steel and aluminum, as well as polyester surfaces.

PHISICAL AND CHEMICAL CHARACTERISTICS

VOC content: 2004/42/IIB(b)(250) < 250 g/l


Shelf life: 9 months. Density: 2 - 2,1 g/cm³

COLOUR: Dark Grey

APPLICATION AND USE

The surface must be clean, dry, degreased and matt with abrasives. Mix well the putty in weight with 2-3% catalyst. Apply within 3 to 5 minutes at 20oC. A higher temperature can reduce service life and accelerate drying time.

Note: Using too much hardener may cause discoloration of the top layer. Putty below 15°C is not recommended. Do not apply over one-component wash primers and acrylic products.



Limpieza


25 -30 s



Adición de catalizador

Masilla 100 g

Catalizador. 2-3 g



Tiempo de aplicación

3-5 min.


Tiempo de secado


20 – 30 min.


Lijado a mano / seco

P150 – P320


Lijado a máquina / seco

P150 – P320


Almacenar en lugar frío.

SECURITY INFORMATION

See Security data sheet.

STORAGE AND SHELF LIFE

12 months, if kept under proper storage conditions.

AVAILABLE PACKAGING

Code	Description	Packaging
5006-001081	FILL FLEX	1KG

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.