



DESCRIPTION

Quick Mix Multifix is a two-component cyanoacrylate adhesive that is ideal for various repairs. It has the best adhesive properties on many different materials.

- Fast curing
- Extremely shock resistant
- Large filling capacity
- For quick professional repairs

APPLICATIONS

Its excellent gap filling properties (up to 0.8 mm) make it particularly suitable for adhesive applications where an adhesive gap is required. Due to its consistency, Quick Mix Multifix is ultra drip-free and you can use it horizontally or vertically. Quick Mix Multifix is extremely impact resistant and machine workable, making it ideal for quick and easy permanent bond repairs. Quick Mix Multifix has excellent adhesive properties on many materials: metal, rubber, porous / absorbent materials such as wood, paper, cardboard, leather, textile and many plastics such as: PVC, ABS, PC, PBT.

INSTRUCTIONS

Always ensure that the surface to be bonded is clean, dry and free of grease. For best results, always store Quick Mix Multifix ultra in the refrigerator.

TECHNICAL DATA

Chemical type: Methoxethyl – cyanacrylate

Mixing ratio: 4 to 1

Colour: Transparent

Viscosity A-comp. (mpas): 175.000-200.000

Viscosity B-comp. (mpas): 20-100

Density (g/ml):

A-component: 1,05 – 1,07

B-component: 1,15 – 1,16

Flashpoint: +87°

Application temperature: optimal at +23°

Stretch: 200%

Working time: 2 minutes

Fixing time (joined) seconds:

Steel 5-10

Steel (sand blasted) 10-15

Stainless steel 15-20

Aluminum 5-10

Polycarbonate 10-15 ABS 20-30

PMMA 70-90

Pine wood 30-45

Beech wood 7-15

Final strength after: 8 hours

SPECIFICATIONS HARDENER PRODUCT

Tensile shear strenght (N/m²): 14-16

Service temperature range (°C) : -10 to +40

Temperature range (°C): -40 to +100

Maximum gap filling: 0,8 mm

SECURITY INFORMATION

See Security data sheet.

STORAGE AND SHELF LIFE

The shelf life of QUICK MIX EXPRESS 50 ML is 12 months from the date of production, as long as it is stored in a cool and dry place, temperature varying between +10°C and 25°C. The expiry date is indicated on the label.

AVAILABLE PACKAGING

Code	Description	Packaging
5006-001094	QUICK MIX MULTIFIX	10GR

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.