



DESCRIPTION

QUICK ZINC-ALU is a product formulated with very fast drying thermoplastic acrylic resins, together with zinc powder and aluminium.

APPLICATION

Due to the characteristics of the product we recommend its use in the automotive sector. They give the surfaces a galvanised metallic appearance, which is very suitable for touching up defects on parts that have been treated with galvanic systems.

CHARACTERISTICS

- Very fast drying.
- Good adhesion.
- Excellent corrosion resistance.
- High gloss durability.
- Lead-free.
- Ease of application and recoating.
- High hiding power.

Physical characteristics		Packaging characteristics	
Binder type	Thermoplastic acrylic	Rated capacity	400 ml
Colour	Silver	Heat resistance of the packaging	<50 °C
Brightness	Satin	Propellant	LPG C3-C4
Zinc content	66 %		

Touch-drying (ASTM D-1640 ISO 1517)	10'		
Total drying (ASTM D-1640 ISO 1517)	30'		
Dry film thickness	25 µ/coat (2 passes)		
Adhesion (ASTM D-3359 ISO 2409)	3B		
Salt spray	300 h		
Theoretical performance	2 m ² for aerosol 400 ml		
Diluent	Butyl acetate		
Product life	> 2 years		
Repainting	After 10'.		
Resistance of the paint to heat	300 °C - 500 °C		
Conditions of application	Minimum ambient temperature: 8 °C	T° Surface min: 5-50 °C	Max. humidity 85 % R.H.P.

* Adhesion tests have been carried out on steel plates.

MODE OF APPLICATION

- Shake the aerosol very well before use, approximately one minute after hearing the noise of the mixer.
- Apply on clean and dry surfaces. Remove corrosion with a wire brush.
- Apply in thin coats for best results, three thin coats are always better than one thick coat, repaintable after ten minutes with the same paint.

- Invert the aerosol to purge the valve after use, if the diffuser clogs replace it with a new one.
- Do not apply to connected equipment and use in well ventilated areas.
- Ask for safety data sheets.

SECURITY INFORMATION

See Safety Data Sheet.

PACKAGING AVAILABLE:

Code	Description	Packaging
5011-001075	QUICK ZINC-ALU	400ML

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee the perfect quality of the product. However, considering that the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.