



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099




Version: 7

Revision: 28/06/2023




Previous revision: 22/09/2022

Date of printing: 28/06/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 **PRODUCT IDENTIFIER:**
FILL UNIVERSAL
Code : 5001-001098/5001-001090/5001-001099 UFI: 72HE-VVPM-Q208-3E1W
- 1.2 **RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:**
Intended uses (main technical functions): ☒ Industrial ☒ Professional ☐ Consumers
Putty
Sectors of use:
Professional uses (SU22).
Uses advised against:
This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as "Intended or identified uses". This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet.
Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:
Not restricted.
- 1.3 **DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:**
CAR REPAIR SYSTEM S.A.
Pol.Ind. 2 de Octubre, c/ José Muñoz 6 - 18320 Santa Fe - Granada ESPAÑA
Phone number: (+34) 95 8431792 - www.carrepairsystem.eu
- E-mail address of the person responsible for the Safety Data Sheet:
info@carrepairsystem.eu
- 1.4 **EMERGENCY TELEPHONE NUMBER:**
(+34) 95 8431792 L-J 8:30-14 / 15-18 h. V 8:30-14:30 h.
 National Poisons Information Service (NPIS) - In England, Wales or Scotland: dial 111 - In N Ireland: contact your local GP or pharmacist during normal hours.

SECTION 2 : HAZARDS IDENTIFICATION

- 2.1 **CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:**
Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.
Classification in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP):
DANGER:Flam. Liq. 3:H226|Skin Irrit. 2:H315|Eye Irrit. 2:H319|Skin Sens. 1:H317|Repr. 2:H361d|STOT RE 1:H372|Aquatic Chronic 4:H413
- | Danger class | Classification of the mixture | Cat. | Routes of exposure | Target organs | Effects |
|--|--|---|---|---|---|
| Physicochemical:  | Flam. Liq. 3:H226 c) | Cat.3 | - | - | - |
| Human health:  | Skin Irrit. 2:H315 c)
Eye Irrit. 2:H319 c)
Skin Sens. 1:H317 c)
Repr. 2:H361d c)
STOT RE 1:H372 c) | Cat.2
Cat.2
Cat.1
Cat.2
Cat.1 | Skin
Eyes
Skin
-
Inhalation | Skin
Eyes
Skin
Reproductive system
Systemic | Irritation
Irritation
Allergy
Foetus
Damage |
| Environment: | Aquatic Chronic 4:H413 c) | Cat.4 | - | - | - |
- Full text of hazard statements mentioned is indicated in section 16.
- Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.
- 2.2 **LABEL ELEMENTS:**
-  This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP)
- Hazard statements:
- H226 Flammable liquid and vapour.
H361d Suspected of damage the unborn child.
H372 Causes damage to hearing organs through prolonged or repeated exposure if inhaled.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H413 May cause long lasting harmful effects to aquatic life.
- Precautionary statements:
- P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection.

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2020/878

Page 2/14
(Language:EN)

FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

	<p>P305+P351+P338- P310 P308+P313 P405 P501</p> <p>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. IF exposed or concerned: Get medical attention. Store locked up. Dispose of contents/container to hazardous or special waste collection point.</p> <p><u>- Supplementary statements:</u> EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</p> <p><u>- Substances that contribute to classification:</u> Styrene Maleic anhydride</p> <p><u>Other sensitizing components:</u> 2,2"-(m-tolylimino)diethanol</p>										
2.3	<p><u>OTHER HAZARDS:</u> Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:</p> <p><u>- Other physicochemical hazards:</u> Vapours may form with air a mixture potentially flammable or explosive.</p> <p><u>- Other adverse human health effects:</u> Prolonged exposure to vapours may produce transient drowsiness. Prolonged contact may cause skin dryness.</p> <p><u>- Other negative environmental effects:</u> Does not contain substances that fulfil the PBT/vPvB criteria.</p> <p><u>Endocrine disrupting properties:</u> This product does not contain substances with endocrine disrupting properties identified or under evaluation.</p>										
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS											
3.1	<p><u>SUBSTANCES:</u> Not applicable (mixture).</p>										
3.2	<p><u>MIXTURES:</u> This product is a mixture.</p> <p><u>Chemical description:</u> Filler</p> <p><u>HAZARDOUS INGREDIENTS:</u> Substances taking part in a percentage higher than the exemption limit:</p> <table border="1"> <tr> <td>10 < C ≤ 15 %</td><td>Styrene CAS: 100-42-5, EC: 202-851-5, REACH: 01-2119457861-32 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 (ATE=11800 mg/m3) Skin Irrit. 2:H315 Eye Irrit. 2:H319 Repr. 2:H361d STOT SE (irrit.) 3:H335 STOT RE 1:H372 Asp. Tox. 1:H304 Aquatic Chronic 3:H412</td><td>REACH</td></tr> <tr> <td>C < 1 %</td><td>2,2"-(m-tolylimino)diethanol CAS: 91-99-6, EC: 202-114-8, REACH: 01-2120791683-42 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=1000 mg/kg) Skin Irrit. 2:H315 Eye Dam. 1:H318 STOT RE 2:H373 Skin Sens. 1B:H317</td><td>Autoclassified REACH</td></tr> <tr> <td>C ≤ 0,05 %</td><td>Maleic anhydride CAS: 108-31-6, EC: 203-571-6, REACH: 01-2119472428-31 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=481 mg/kg) Skin Corr. 1B:H314 Eye Dam. 1:H318 Resp. Sens. 1:H334 STOT RE 1:H372 EUH071 Skin Sens. 1A:H317</td><td>REACH / ATP13 Skin Sens. 1A, H317: C ≥ 0,001 %</td></tr> </table>	10 < C ≤ 15 %	Styrene CAS: 100-42-5, EC: 202-851-5, REACH: 01-2119457861-32 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 (ATE=11800 mg/m3) Skin Irrit. 2:H315 Eye Irrit. 2:H319 Repr. 2:H361d STOT SE (irrit.) 3:H335 STOT RE 1:H372 Asp. Tox. 1:H304 Aquatic Chronic 3:H412	REACH	C < 1 %	2,2"-(m-tolylimino)diethanol CAS: 91-99-6, EC: 202-114-8, REACH: 01-2120791683-42 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=1000 mg/kg) Skin Irrit. 2:H315 Eye Dam. 1:H318 STOT RE 2:H373 Skin Sens. 1B:H317	Autoclassified REACH	C ≤ 0,05 %	Maleic anhydride CAS: 108-31-6, EC: 203-571-6, REACH: 01-2119472428-31 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=481 mg/kg) Skin Corr. 1B:H314 Eye Dam. 1:H318 Resp. Sens. 1:H334 STOT RE 1:H372 EUH071 Skin Sens. 1A:H317	REACH / ATP13 Skin Sens. 1A, H317: C ≥ 0,001 %	
10 < C ≤ 15 %	Styrene CAS: 100-42-5, EC: 202-851-5, REACH: 01-2119457861-32 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 (ATE=11800 mg/m3) Skin Irrit. 2:H315 Eye Irrit. 2:H319 Repr. 2:H361d STOT SE (irrit.) 3:H335 STOT RE 1:H372 Asp. Tox. 1:H304 Aquatic Chronic 3:H412	REACH									
C < 1 %	2,2"-(m-tolylimino)diethanol CAS: 91-99-6, EC: 202-114-8, REACH: 01-2120791683-42 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=1000 mg/kg) Skin Irrit. 2:H315 Eye Dam. 1:H318 STOT RE 2:H373 Skin Sens. 1B:H317	Autoclassified REACH									
C ≤ 0,05 %	Maleic anhydride CAS: 108-31-6, EC: 203-571-6, REACH: 01-2119472428-31 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=481 mg/kg) Skin Corr. 1B:H314 Eye Dam. 1:H318 Resp. Sens. 1:H334 STOT RE 1:H372 EUH071 Skin Sens. 1A:H317	REACH / ATP13 Skin Sens. 1A, H317: C ≥ 0,001 %									
	<p><u>Impurities:</u> Does not contain other components or impurities which will influence the classification of the product.</p> <p><u>Stabilizers:</u> None.</p> <p><u>Reference to other sections:</u> For more information on hazardous ingredients, see sections 8, 11, 12 and 16.</p> <p><u>SUBSTANCES OF VERY HIGH CONCERN (SVHC):</u> List updated by ECHA on 17/01/2023. <u>Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:</u> None. <u>Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:</u> None.</p> <p><u>PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:</u> Does not contain substances that fulfil the PBT/vPvB criteria.</p>										



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022





Date of printing: 28/06/2023

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid. It can be dangerous to the person giving artificial respiration by mouth-to-mouth (the kiss of life).

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation: 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin: 	Skin contact causes redness. Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
Eyes: 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
Ingestion: 	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician:

The product inhaled during vomiting could cause lung damage. Thus, emesis should not be induced, neither mechanically nor pharmacologically. In the case of ingestion, empty the stomach with caution.

Antidotes and contraindications:

Specific antidote not known. In the case of a pneumonia by chemical agents, must be considered a therapy with antibiotics and corticosteroids.

SECTION 5: FIREFIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

Extinguishing powder or CO₂.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide, nitrogen oxides. Exposure to combustion or decomposition products may be a hazard to health.

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment:

Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations:

Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1** PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
- 6.2** ENVIRONMENTAL PRECAUTIONS:
Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
- 6.3** METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:
Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Keep the remains in a closed container.
- 6.4** REFERENCE TO OTHER SECTIONS:
For contact information in case of emergency, see section 1.
For information on safe handling, see section 7.
For exposure controls and personal protection measures, see section 8.
For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

- 7.1** PRECAUTIONS FOR SAFE HANDLING:
Comply with the existing legislation on health and safety at work.
- General recommendations:
Avoid any type of leakage or escape. Keep the container tightly closed.
- Recommendations for the prevention of fire and explosion risks:
Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. If this product is used in an industrial installation, the zones with risk of explosion should be marked. Use instruments, systems and protective equipment adequate to the classification of zones, according to the health and safety at work laws, in accordance with Directive 2016/34/EU and 99/92/EC. Electrical equipment should be protected to the appropriate standard. No tools with a potential for sparks should be used. Elaborate the document "Protection against explosions".
Flashpoint 31* °C (Pensky-Martens) CLP 2.6.4.3.
Autoignition temperature: 490 °C
- Recommendations for the prevention of toxicological risks:
Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.
- Recommendations for the prevention of environmental contamination:
It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.
- 7.2** CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
Keep locked up. Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.
- Class of store:
According to current legislation.
- Maximum storage period:
6 Months.
- Temperature interval:
min: 5 °C, max: 40 °C (recommended).
- Incompatible materials:
Keep away from water, oxidizing agents, alkalis, amines, alcohols, acids, peroxides, polymerization initiators.
- Type of packaging:
According to current legislation.
- Limit quantity (Seveso III): Directive 2012/18/EU:
- Named dangerous substances/mixtures: None
- Hazard categories and lower-/upper threshold quantities in tonnes (t):
· Physical hazards: Flammable liquid and vapour. (P5c) (5000t/50000t).
· Health hazards: Not applicable
· Environmental hazards: Not applicable
· Other hazards: Not applicable
- Threshold quantity for the application of lower-tier requirements: 5000 tons
- Threshold quantity for the application of upper-tier requirements: 50000 tons
- Remarks:
The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.
- 7.3** SPECIFIC END USE(S):
For the use of this product particular recommendations apart from that already indicated are not available.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

EH40/2005 WELs (United Kingdom) 2018	Year	WEL-TWA		WEL-STEL		Remarks
		ppm	mg/m ³	ppm	mg/m ³	
Styrene	1997	20	85	40	170	BMGV, A4
Maleic anhydride	2014	0,01	0,4	-	-	Sc, Si, A4, FIV

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

BMGV - Biological monitoring guidance value. BMGVs are non-statutory and any biological monitoring undertaken in association with a guidance value needs to be conducted on a voluntary basis (ie with the fully informed consent of all concerned).

Sc - May cause sensitization by skin contact.

Si - May cause sensitization by inhalation.

A4 - Non classified as carcinogenic in humans.

- Inhalable fraction and vapour (IFV):

IFV notation indicates those chemical agents that may occur in the workplace, both as particulate matter and as vapour, so that the two phases can coexist, both contributing to exposure. This situation can occur mainly in the following cases: a) When the agent in question has an 'intermediate' value of the vapour pressure (in these cases it is taking into account the relationship between its concentration in air saturated vapour and the value of TWA, and the note is assigned, generally, when the ratio between the two quantities is between 0.1 and 10), b) Because of the form of use of the chemical agent (e.g. spraying), c) In the processes involving large temperature changes that may affect the physical state of the chemical agent, and d) In the processes in which a significant fraction of vapour can be dissolved or adsorbed onto particles of other substances, like what happens with water soluble agents in high humidity environments. For more information, see C.Perez and S.C.Soderholm. Some chemicals requiring special consideration when deciding whether to sample the particle, vapor or both phases of an atmosphere. Appl. Occup. Environ. Hyg. 6 (10), 859-864. 1991).

- BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

- Styrene (2014): 1°) Biological determinant: mandelic acid plus phenylglyoxylic acid in urine, BEI: 400 mg/g creatinine, Sampling time: end of shift (2). Notation: (Ns). 2°) Biological determinant: styrene in urine, BEI: 40 µg/l, Sampling time: end of shift (2).

These indicators accumulate in the body during the work week, therefore the sampling time is critical in relation to previous exposures. (2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases. Once the steady state that depends on each biological indicator (weeks, months) has been reached, sampling of these can be done at any time. &The biological determinant is an indicator of exposure to the chemical, but the quantitative interpretation of the measurement is ambiguous. &(CDC: Guidelines for the identification and management of lead exposure in pregnant and lactating women, 2010).

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m ³		DNEL Cutaneous mg/kg bw/d		DNEL Oral mg/kg bw/d	
	(a)	(c)	(a)	(c)	(a)	(c)
2,2"-(m-tolylimino)diethanol	0,8	0,8	s/r	0,23	-	-
Styrene	100	85	b/r	406	-	-
Maleic anhydride	0,8	0,4	a/r	-	-	-

- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m ³		DNEL Cutaneous mg/cm ²		DNEL Eyes mg/cm ²	
	(a)	(c)	(a)	(c)	(a)	(c)
2,2"-(m-tolylimino)diethanol	m/r	m/r	m/r	m/r	m/r	-
Styrene	100	100	b/r	b/r	b/r	-
Maleic anhydride	0,8	0,4	a/r	a/r	a/r	-

- Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

b/r - DNEL not derived (low hazard).

m/r - DNEL not derived (medium hazard).

a/r - DNEL not derived (high hazard).



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

<u>- PREDICTED NO-EFFECT CONCENTRATION. AQUATIC ORGANISMS:- Fresh water, marine water and intermittent release:</u>	<u>PNEC Fresh water</u> mg/l	<u>PNEC Marine</u> mg/l	<u>PNEC Intermittent</u> mg/l
2,2"-(m-tolylimino)diethanol	0.107	0.0107	1.07
Styrene	0.04	0.04	0.04
Maleic anhydride	0.1	0.01	-
<u>- WASTEWATER TREATMENT PLANTS (STP) AND SEDIMENTS IN FRESH- AND MARINE WATER:</u>	<u>PNEC STP</u> mg/l	<u>PNEC Sediments</u> mg/kg dw/d	<u>PNEC Sediments</u> mg/kg dw/d
2,2"-(m-tolylimino)diethanol	81.7	2.16	0.22
Styrene	5	0.614	0.418
Maleic anhydride	44.6	0.334	0.0334
<u>- PREDICTED NO-EFFECT CONCENTRATION. TERRESTRIAL ORGANISMS:- Air, soil and effects for predators and humans:</u>	<u>PNEC Air</u> mg/m3	<u>PNEC Soil</u> mg/kg dw/d	<u>PNEC Oral</u> mg/kg dw/d
2,2"-(m-tolylimino)diethanol	s/r	0.37	n/b
Styrene	s/r	0.2	n/b
Maleic anhydride	s/r	0.042	n/b

n/b - PNEC not derived (not bioaccumulative potential).

s/r - PNEC not derived (not identified hazard).

8.2

EXPOSURE CONTROLS:ENGINEERING MEASURES:

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

- Protection of respiratory system:

Avoid the inhalation of vapours. Avoid the inhalation of dust.

- Protection of eyes and face:

It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area.

- Protection of hands and skin:

It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask: 	✓ A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.
Safety goggles: 	✓ Safety goggles with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.
Gloves: 	✓ Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:	No.
Apron:	No.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

Clothing: Advisable.

- Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment of the product, wastes, packages or spraybooth sewages.

- Spills on the soil:

Prevent contamination of soil.

- Spills in water:

Do not allow to escape into drains, sewers or water courses.

-Water Management Act:

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

VOC (product ready for use*):

It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: VEHICLE REFINISHING PRODUCTS (defined in the Directive 2004/42/EC, Annex I.2): Emission subcategory B) Bodyfiller. VOC (product ready for use*): (FILL UNIVERSAL Cod. 5001-001098 = 100 in volume): 31,9 g/l* (VOC max.250 g/l* starting from 01.01.2010)

VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 15,00 % Weight, VOC (supply): 2,10 % Weight, VOC: 1,42 % C (expressed as carbon), Molecular weight (average): 83,90 , Number C atoms (average): 4,74

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:Appearance

Physical state:

Paste

Colour:

Beige

Odour:

Characteristic

Odour threshold:

Not available (mixture).

Change of state

Softening point/range:

Not available (mixture).

Initial boiling point:

145 °C at 760 mmHg

- Flammability:

Flashpoint

31* °C (Pensky-Martens)

CLP 2.6.4.3.

Lower/upper flammability or explosive limits:

Not available - Not available

Autoignition temperature:

490 °C

Stability

Decomposition temperature:

Not available (technical impossibility to obtain the data).

pH-value

pH:

Not applicable (non-aqueous media).

- Viscosity:

Dynamic viscosity:

Not available.

Kinematic viscosity:

Not available.

Viscosity (flow time):

Not available.

- Solubility(ies):

Solubility in water

Liposolubility:

Not applicable (inorganic product).

Partition coefficient: n-octanol/water:

Not applicable (mixture).

- Volatility:

Vapour pressure:

5* mmHg at 20°C

Vapour pressure:

6,67 hPa at 20°C

Vapour pressure:

3,3004* kPa at 50°C

Evaporation rate:

Not available (lack of data).

Density

Relative density:

1,520* at 20/4°C

Relative water

Relative vapour density:

Not available.

Particle characteristics

Particle size:

Not available.

- Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

- Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

9.2

OTHER INFORMATION:Information regarding physical hazard classes

Flammable liquids: Combustibility:

Combustible.

Other security features:

Heat of combustion:

4119 Kcal/kg

VOC (supply):

2,1 % Weight

VOC (supply):

250,0 g/l

Nonvolatile:

84,45 * % Weight

1h. 60°C

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10: STABILITY AND REACTIVITY

10.1

REACTIVITY:- Corrosivity to metals:

It is not corrosive to metals.

- Pyrophorical properties:

It is not pyrophoric.

10.2

CHEMICAL STABILITY:

Stable under recommended storage and handling conditions.

10.3

POSSIBILITY OF HAZARDOUS REACTIONS:

Possible dangerous reaction with water, oxidizing agents, alkalis, amines, alcohols, acids, peroxides, polymerization initiators.

10.4

CONDITIONS TO AVOID:- Heat:

Keep away from sources of heat.

- Light:

If possible, avoid direct contact with sunlight.

- Air:

The product is not affected by exposure to air, but should not be left the containers open.

- Humidity:

Avoid extreme humidity conditions.

- Pressure:

Not relevant.

- Shock:

The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

10.5

INCOMPATIBLE MATERIALS:

Keep away from water, oxidizing agents, alkalis, amines, alcohols, acids, peroxides, polymerization initiators.

10.6

HAZARDOUS DECOMPOSITION PRODUCTS:

As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

11.1 INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 :

ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m3·4h Inhalation
2,2'-(m-tolylimino)diethanol	> 1000 Rat	> 2000 Rat	
Styrene	> 5000 Rat	> 2000 Rabbit	> 11800 Rat
Maleic anhydride	481 Rat	2620 Rabbit	> 720 Rat
Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m3·4h Inhalation
2,2'-(m-tolylimino)diethanol	> 1000	-	-
Styrene	-	-	11800 Vapours
Maleic anhydride	481	-	-

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level	NOAEL Oral mg/kg bw/d	NOAEL Cutaneous mg/kg bw/d	NOAEC Inhalation mg/m3
Styrene	1000 Rat		

Lowest observed adverse effect level	LOAEL Oral mg/kg bw/d	LOAEL Cutaneous mg/kg bw/d	LOAEC Inhalation mg/m3
2,2'-(m-tolylimino)diethanol	50 Rat		
Styrene	2000 Rat		

INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Skin: Not classified	ATE > 2000 mg/kg bw	Not available.	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Respiratory corrosion/irritation: Not classified		-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: 	Skin 	Cat.2	IRRITANT: Causes skin irritation.	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified		-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: 	Skin 	Cat.1	SENSITISING: May cause an allergic skin reaction.	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Neurological:	RE	Systemic	Cat.1	NEUROTOXIC: Causes damage to hearing organs through prolonged or repeated exposure if inhaled (loss of audition).	GHS/CLP 3.8.3.4

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

- Effects via lactation:

Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

- Short-term exposure:

Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours. Causes skin irritation. Very small amounts aspirated by the lungs may cause severe pulmonary damage, including death.

- Long-term or repeated exposure:

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Causes damage to hearing organs through prolonged or repeated exposure if inhaled.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOKINETICS, METABOLISM AND DISTRIBUTION:

- Dermal absorption:

Not available.

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

Not available.

11.2 INFORMATION ON OTHER HAZARDS:

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

Other information:

No additional information available.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

SECTION 12: ECOLOGICAL INFORMATION

	No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).																																															
12.1	TOXICITY: <table><tr><td>- Acute toxicity in aquatic environment for individual ingredients</td><td>CL50 (OECD 203) mg/l · 96hours</td><td>CE50 (OECD 202) mg/l · 48hours</td><td>CE50 (OECD 201) mg/l · 72hours</td></tr><tr><td>2,2"-(m-tolylimino)diethanol</td><td>102 - Fishes</td><td>107 - Daphniae</td><td></td></tr><tr><td>Styrene</td><td>4 - Fishes</td><td>4.7 - Daphniae</td><td>4.9 - Algae</td></tr><tr><td>Maleic anhydride</td><td>230 - Fishes</td><td>330 - Daphniae</td><td>150 - Algae</td></tr></table> <table><tr><td>- No observed effect concentration</td><td>NOEC (OECD 210) mg/l · 28 days</td><td>NOEC (OECD 211) mg/l · 21 days</td><td>NOEC (OECD 201) mg/l · 72 hours</td></tr><tr><td>2,2"-(m-tolylimino)diethanol</td><td></td><td>100 - Daphniae</td><td></td></tr><tr><td>Styrene</td><td></td><td>1 - Daphniae</td><td></td></tr><tr><td>Maleic anhydride</td><td></td><td>10 - Daphniae</td><td>150 - Algae</td></tr></table> - Lowest observed effect concentration Not available ASSESSMENT OF AQUATIC TOXICITY: <table><tr><td>Aquatic toxicity</td><td>Cat.</td><td>Main hazards to the aquatic environment</td><td>Criteria</td></tr><tr><td>- Acute aquatic toxicity: Not classified</td><td>-</td><td>Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).</td><td>GHS/CLP 4.1.3.5.5.3.</td></tr><tr><td>- Chronic aquatic toxicity: Not classified</td><td>Cat.4</td><td>May cause long lasting harmful effects to aquatic life.</td><td>GHS/CLP 4.1.3.5.5.4.</td></tr></table> CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components. CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.				- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours	2,2"-(m-tolylimino)diethanol	102 - Fishes	107 - Daphniae		Styrene	4 - Fishes	4.7 - Daphniae	4.9 - Algae	Maleic anhydride	230 - Fishes	330 - Daphniae	150 - Algae	- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours	2,2"-(m-tolylimino)diethanol		100 - Daphniae		Styrene		1 - Daphniae		Maleic anhydride		10 - Daphniae	150 - Algae	Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria	- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.	- Chronic aquatic toxicity: Not classified	Cat.4	May cause long lasting harmful effects to aquatic life.	GHS/CLP 4.1.3.5.5.4.
- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours																																													
2,2"-(m-tolylimino)diethanol	102 - Fishes	107 - Daphniae																																														
Styrene	4 - Fishes	4.7 - Daphniae	4.9 - Algae																																													
Maleic anhydride	230 - Fishes	330 - Daphniae	150 - Algae																																													
- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours																																													
2,2"-(m-tolylimino)diethanol		100 - Daphniae																																														
Styrene		1 - Daphniae																																														
Maleic anhydride		10 - Daphniae	150 - Algae																																													
Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria																																													
- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.																																													
- Chronic aquatic toxicity: Not classified	Cat.4	May cause long lasting harmful effects to aquatic life.	GHS/CLP 4.1.3.5.5.4.																																													
12.2	PERSISTENCE AND DEGRADABILITY: - Biodegradability: Not readily biodegradable. <table><tr><td>Aerobic biodegradation for individual ingredients</td><td>COD mgO2/g</td><td>%DBO/DQO 5 days 14 days 28 days</td><td>Biodegradabilidad</td></tr><tr><td>2,2"-(m-tolylimino)diethanol</td><td></td><td>- - -</td><td>Not easy</td></tr><tr><td>Styrene</td><td>2800</td><td>87 - -</td><td>Easy</td></tr><tr><td>Maleic anhydride</td><td>979</td><td>41 75 97</td><td>Easy</td></tr></table> Note: Biodegradability data correspond to an average of data from various bibliographic sources. - Hydrolysis: Not available. - Photodegradability: Not available.				Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad	2,2"-(m-tolylimino)diethanol		- - -	Not easy	Styrene	2800	87 - -	Easy	Maleic anhydride	979	41 75 97	Easy																												
Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad																																													
2,2"-(m-tolylimino)diethanol		- - -	Not easy																																													
Styrene	2800	87 - -	Easy																																													
Maleic anhydride	979	41 75 97	Easy																																													
12.3	BIOACCUMULATIVE POTENTIAL: Not available. <table><tr><td>Bioaccumulation for individual ingredients</td><td>logPow</td><td>BCF L/kg</td><td>Potential</td></tr><tr><td>2,2"-(m-tolylimino)diethanol</td><td>1.9</td><td></td><td>Unlikely, low</td></tr><tr><td>Styrene</td><td>2.96</td><td></td><td>No bioaccumulable</td></tr><tr><td>Maleic anhydride</td><td>-2.61</td><td>5.4 (calculated)</td><td>No bioaccumulable</td></tr></table>				Bioaccumulation for individual ingredients	logPow	BCF L/kg	Potential	2,2"-(m-tolylimino)diethanol	1.9		Unlikely, low	Styrene	2.96		No bioaccumulable	Maleic anhydride	-2.61	5.4 (calculated)	No bioaccumulable																												
Bioaccumulation for individual ingredients	logPow	BCF L/kg	Potential																																													
2,2"-(m-tolylimino)diethanol	1.9		Unlikely, low																																													
Styrene	2.96		No bioaccumulable																																													
Maleic anhydride	-2.61	5.4 (calculated)	No bioaccumulable																																													
12.4	MOBILITY IN SOIL: Not available <table><tr><td>Mobility for individual ingredients</td><td>log Pod</td><td>Constant of Henry Pa · m3/mol 20°C</td><td>Potential</td></tr><tr><td>2,2"-(m-tolylimino)diethanol</td><td>2,22</td><td></td><td>Unlikely, low</td></tr><tr><td>Styrene</td><td>2,55</td><td>231,6 (calculated)</td><td>No bioaccumulable</td></tr><tr><td>Maleic anhydride</td><td>1,36</td><td></td><td>No bioaccumulable</td></tr></table>				Mobility for individual ingredients	log Pod	Constant of Henry Pa · m3/mol 20°C	Potential	2,2"-(m-tolylimino)diethanol	2,22		Unlikely, low	Styrene	2,55	231,6 (calculated)	No bioaccumulable	Maleic anhydride	1,36		No bioaccumulable																												
Mobility for individual ingredients	log Pod	Constant of Henry Pa · m3/mol 20°C	Potential																																													
2,2"-(m-tolylimino)diethanol	2,22		Unlikely, low																																													
Styrene	2,55	231,6 (calculated)	No bioaccumulable																																													
Maleic anhydride	1,36		No bioaccumulable																																													
12.5	RESULTS OF PBT AND VPVB ASSESMENT:(Annex XIII of Regulation (EC) no. 1907/2006:) Does not contain substances that fulfil the PBT/vPvB criteria.																																															
12.6	ENDOCRINE DISRUPTING PROPERTIES: This product does not contain substances with endocrine disrupting properties identified or under evaluation.																																															
12.7	OTHER ADVERSE EFFECTS: - Ozone depletion potential: Not available.																																															



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

- [Photochemical ozone creation potential:](#)

Not available.

- [Earth global warming potential:](#)

In case of fire or incineration liberates CO2.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 [WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation \(EU\) no. 1357/2014:](#)

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

[Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:](#)

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

[Procedures for neutralising or destroying the product:](#)

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 [UN NUMBER OR ID NUMBER:](#)

1866

14.2 [UN PROPER SHIPPING NAME:](#)

RESIN SOLUTION

14.3 [TRANSPORT HAZARD CLASS\(ES\):](#)

[Transport by road \(ADR 2023\) and](#)

[Transport by rail \(RID 2023\):](#)

Good not submitted to ADR.

Transport for viscous liquids in packages with capacity under 450 L according to 2.2.3.1.5. (ADR) or under 30 L according to 2.3.2.5. (IMDG).

[Transport by sea \(IMDG 40-20\):](#)

- Class: 3
 - Packing group: III
 - Emergency Sheet (EmS): F-E, S_E
 - First Aid Guide (MFAG): 310
 - Marine pollutant: No.
 - Transport document: Shipping Bill of lading.



[Transport by air \(ICAO/IATA 2021\):](#)

- Class: 3
 - Packing group: III
 - Transport document: Air Bill of lading.



[Transport by inland waterways \(ADN\):](#)

Not available

14.4 [PACKING GROUP:](#)

See section 14.3

14.5 [ENVIRONMENTAL HAZARDS:](#)

Not applicable (not classified as hazardous for the environment).

14.6 [SPECIAL PRECAUTIONS FOR USER:](#)

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

14.7 [MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:](#)

Not available.



FILL UNIVERSAL

Code : 5001-001098/5001-001090/5001-001099



Version: 7

Revision: 28/06/2023

Previous revision: 22/09/2022

Date of printing: 28/06/2023

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use:

See section 1.2

Tactile warning of danger:

Not applicable (product for professional or industrial use).

Child safety protection:

Not applicable (product for professional or industrial use).

VOC information on the label:

Contains VOC max. 31,9 g/l* for the product ready for use - The limit value 2004/42/EC-IIB cat. B) Bodyfiller. is VOC max. 250 g/l

OTHER REGULATIONS:

Not available.

Control of the risks inherent in major accidents (Seveso III):

See section 7.2

Other local legislations:

The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETY ASSESSMENT:

A chemical safety assessment has not been carried out for this mixture.

SECTION 16 : OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2021/849 (CLP), Annex III:

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. EUH071 Corrosive to the respiratory tract. H361d Suspected of damage the unborn child. H372 Causes damage to respiratory system through prolonged or repeated exposure if inhaled. H373 May cause damage to kidneys through prolonged or repeated exposure if swallowed. H372 Causes damage to hearing organs through prolonged or repeated exposure if inhaled.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2021).
- European agreement on the international carriage of dangerous goods by road, (ADR 2023).
- International Maritime Dangerous Goods Code IMDG including Amendment 40-20 (IMO, 2020).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Code : 5001-001098/5001-001090/5001-001099



Date of printing: 28/06/2023

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.