



DESCRIPTION

QUICK PRO- PEEL CABIN is a sprayable water-based product that creates a masking film for the protection of spray booth surfaces. It protects walls from overspray and paint overspray. The dry product is completely transparent, preventing the distortion of brightness inside the booth. This product forms a protective, peelable and washable film on spray booth walls.

AREA OF APPLICATION

QUICK PRO-PEEL CABIN is used to protect paint booth interiors, protect vehicles during transport and when it is necessary to park the vehicle in the workshop. Walls and lamps can be protected from splashes and residues with QUICK PRO-PEEL CABIN. It is also suitable for the protection of paint benches and other painting equipment.

For professional use.

TECHNICAL INFORMATION

Aspect	Liquid
Packaging	Carafe / 5 L
Colour	Transparent
Smell	Uncharacteristic
Specific weight	1.03 g/ccm
Application quantity	5-10 litres/cabin (1.5-2 roosters/cabin)
Solubility	Soluble in hot and cold water.

APPLICATION AND FIELD OF USE:

Preparation:

Cleaning, drying and degreasing of spray booth walls.

Application:

Fill a gun with QUICK PRO- PEEL CABIN and adjust the air pressure according to the recommended settings below:

Conventional Spray Gun: gun spray pressure between 40-45 psi, with 1.8-2.2mm fluid nozzle.

HVLP and Gravity Spray Guns: gun spray pressure between 40-45 psi, with 1.8-2.2mm fluid peak.

Apply a wet coat to all surfaces including glass and lights. Avoid drips. Wait for the product to dry completely. Apply a second wet coat. After the second coat has dried, sometimes another wet coat will need to be applied to protect areas such as the lower parts of the cabin walls where higher concentrations of paint can build up.

Note: Before applying to freshly painted cabin walls, make sure they are completely dry.

REMOVE (After 150 applications).

Turn off cabin lights and unplug all electrical systems. QUICK PRO-PEEL CABIN can be removed in the following ways:

Peeling:

Wait until the cabin temperature has dropped to room temperature. The product can be removed from the walls as a film to be peeled off. For hard surfaces (stone or concrete), it is necessary to clean the walls by wetting the product.

Cleanliness:

Wait until the cabin temperature has dropped to room temperature. Spray the walls with water from a hose and let the water take effect for 5 min. For the most heavily soiled parts, use a cleaning cloth or brush. Rinse off the remaining product with a hose. With compressed air, water residues can be removed from the lamps and glass panes. Allow the booth to dry completely. Make sure that all surfaces are perfectly dry before reapplying QUICK PRO-PEEL CABIN.

Efficiency:

The product can be renewed after 3 months or 150 applications. Otherwise, it may be difficult to remove the QUICK PRO-PEEL CABIN film.

STORAGE:

Warning: This product is sensitive to frost.

Shelf life: 12 months at 18 - 20° C closed in its original packaging.

SECURITY INFORMATION

See Safety Data Sheet.

PACKAGING AVAILABLE:

Code	Description	Packaging
5012-000024	QUICK PRO-PEEL CABIN	5 L

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee the perfect quality of the product. However, considering that the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.