MASKING TAPE

2002-001730/40/50/60

EN **TECHNICAL SHEET**

DESCRIPTION

High-quality Masking Tape, ideal for industrial and automotive repair applications, suitable for use at temperatures up to 80°C. It features a saturated paper backing that ensures strength and efficiency.
The adhesive made of natural rubber and solvent resins offers excellent adhesion. This tape is extremely conformable, perfectly adapting to variously shaped surfaces. It is compatible with most common paints and lacquers and can be removed cleanly and without tearing. Additionally, it is easy to tear by hand, facilitating quick and efficient application.
For professional use only.

FEATURES

- Suitable for use up to 80°C
- Saturated paper backing
- Adhesive based on natural rubber and solvent resins
- Excellent conformability to molded surfaces
- Compatible with most paints and lacquers
- Clean, tear-free removal
- Easy to tear by hand

TECHNICAL DATA

Total Weight	59 g/m2
Adhesive	Natural rubber and solvent resins based
Total Thickness	0,125 mm
Adhesion to Steel	4,8 N/25mm
Tensile Strength	87,5 N/25mm
Elongation at Break	8,5%
Temperature Resistance	80°C (30 min)

CAR REPAIR SYSTEM, S.A. Polígono Industrial 2 de Octubre. C./ José Muñoz, 6
18320 Santa Fe (Granada) España - Tel. 00.34. 958.431.792

AVAILABLE PRODUCT

Code	Description	Size	Un/Box
2002-001730	MASKING TAPE	18mm x 45m	96
2002-001740	MASKING TAPE	24mm x 45m	72
2002-001750	MASKING TAPE	36mm x 45m	48
2002-001760	MASKING TAPE	48mm x 45m	36

*For more information on our products or means of application, please visit our website www.carrepairsystem.eu or email us at info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee the perfect quality of the product. However, as the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.

CAR REPAIR SYSTEM, S.A. Polígono Industrial 2 de Octubre. C./ José Muñoz, 6
18320 Santa Fe (Granada) España - Tel. 00.34. 958.431.792