UNIVERSAL THINNER

REF: 5009-001018/5009-001016/5009-001019/5009-001020/5009-001023

EN **TECHNICAL DATA**

DESCRIPTION

Acrylic thinner for acrylic paints, varnishes and acrylic fillers, specifically for use in single and two-coat acrylic paints and enamels. Medium-slow evaporation, suitable for primers, varnishes, acrylic paints and enamels.

CHARACTERISTICS

Specific gravity 20ºC:

- Slow diluent: 0,889 ± 0,010
- Standard diluent: 0,885 ± 0,010

Flammability: 29 ºC.

Boiling range:

- Slow diluent: 126 - 192 ºC.
- Standard diluent: 124 - 185 ºC.

VOC content: 100%.

STORAGE, TOXICITY AND PRECAUTIONS

Store between 5 and 30°C away from moisture and direct sunlight. Refer to MSDS for further handling information.

SURFACE PREPARATION

- Clean with a degreaser suitable for plastics.
- Sanding process according to damage (To be assessed P320 P500 P800 P1500)

CAR REPAIR SYSTEM, S.A. Polígono Industrial 2 de Octubre. C./ José Muñoz, 6
18320 Santa Fe (Granada) Spain - Tel. 00.34. 958.431.792

CAUTION AND CONSIDERATIONS

Product: Must not be discharged directly into sewage system

Treatment accordance with administrative regulations.

Packaging: Disposal in accordance with regulations.

SECURITY INFORMATION

See Safety Data Sheet. For professional use only.

PACKAGING AVAILABLE:

Code	Description	Packaging
5009-001018	SLOW UNIVERSAL THINNER	1 L
5009-001016	SLOW UNIVERSAL THINNER	5 L
5009-001019	STANDARD UNIVERSAL THINNER	1 L
5009-001020	STANDARD UNIVERSAL THINNER	5 L
5009-001023	STANDARD UNIVERSAL THINNER	25 L

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee the perfect quality of the product. However, considering that the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.

CAR REPAIR SYSTEM, S.A. Polígono Industrial 2 de Octubre. C./ José Muñoz, 6
18320 Santa Fe (Granada) Spain - Tel. 00.34. 958.431.792