



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060




Version: 1







Date of issue: 05/06/2024


Date of printing: 05/06/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	PRODUCT IDENTIFIER: QUICK 1K EASY FILLER SPRAY WHITE Code : 5011-001060 UFI: M2ET-MPMK-2013-XUU8
1.2	RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> <input type="checkbox"/> Industrial <input checked="" type="checkbox"/> Professional <input checked="" type="checkbox"/> Consumers Aerosol. <u>Sectors of use:</u> Consumer uses (SU21). <u>Types of PCN use:</u> Chemical products: uncategorised. <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as "Intended or identified uses". This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: CAR REPAIR SYSTEM S.A. Pol.Ind. 2 de Octubre, c/ José Muñoz 6 - 18320 Santa Fe - Granada ESPAÑA Phone number: (+34) 95 8431792 - www.carrepairsystem.eu <u>- E-mail address of the person responsible for the Safety Data Sheet:</u> info@carrepairsystem.eu
1.4	EMERGENCY TELEPHONE NUMBER: (+34) 95 8431792 L-J 8:30-14 / 15-18 h. V 8:30-14:30 h.  National Poisons Information Service (NPIS) - In England, Wales or Scotland: dial 111 - In N Ireland: contact your local GP or pharmacist during normal hours.

SECTION 2 : HAZARDS IDENTIFICATION

2.1	CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2022/692 (CLP):</u> DANGER:Aerosol 1:H222 Eye Irrit. 2:H319 STOT SE (narcosis) 3:H336 Aquatic Chronic 3:H412 EUH066 Aerosol 3:H229																								
	<table border="1"> <thead> <tr> <th>Danger class</th> <th>Classification of the mixture</th> <th>Cat.</th> <th>Routes of exposure</th> <th>Target organs</th> <th>Effects</th> </tr> </thead> <tbody> <tr> <td>Physicochemical: </td> <td>Aerosol 1:H222 c) Aerosol 3:H229 c)</td> <td>Cat.1 Cat.3</td> <td>- -</td> <td>- -</td> <td>- -</td> </tr> <tr> <td>Human health: </td> <td>Eye Irrit. 2:H319 c) STOT SE (narcosis) 3:H336 c) EUH066 c)</td> <td>Cat.2 Cat.3 -</td> <td>Eyes Inhalation Skin</td> <td>Eyes CNS Skin</td> <td>Irritation Narcosis Dryness, Cracking</td> </tr> <tr> <td>Environment:</td> <td>Aquatic Chronic 3:H412 c)</td> <td>Cat.3</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects	Physicochemical: 	Aerosol 1:H222 c) Aerosol 3:H229 c)	Cat.1 Cat.3	- -	- -	- -	Human health: 	Eye Irrit. 2:H319 c) STOT SE (narcosis) 3:H336 c) EUH066 c)	Cat.2 Cat.3 -	Eyes Inhalation Skin	Eyes CNS Skin	Irritation Narcosis Dryness, Cracking	Environment:	Aquatic Chronic 3:H412 c)	Cat.3	-	-	-
Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects																				
Physicochemical: 	Aerosol 1:H222 c) Aerosol 3:H229 c)	Cat.1 Cat.3	- -	- -	- -																				
Human health: 	Eye Irrit. 2:H319 c) STOT SE (narcosis) 3:H336 c) EUH066 c)	Cat.2 Cat.3 -	Eyes Inhalation Skin	Eyes CNS Skin	Irritation Narcosis Dryness, Cracking																				
Environment:	Aquatic Chronic 3:H412 c)	Cat.3	-	-	-																				
	Full text of hazard statements mentioned is indicated in section 16. Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.																								

2.2	LABEL ELEMENTS:  This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2022/692 (CLP).
-----	---

- Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

- Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe vapours.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to ...
[- Supplementary statements:](#)
 EUH208 Contains 4-morpholinecarbaldehyde. May produce an allergic reaction.

[- Substances that contribute to classification:](#)

Acetone
 n-butyl acetate
 2-methoxy-1-methylethyl acetate

2.3

[OTHER HAZARDS:](#)

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

[- Other physicochemical hazards:](#)

No other relevant adverse effects are known.

[- Other adverse human health effects:](#)

No other relevant adverse effects are known.

[- Other negative environmental effects:](#)

Does not contain substances that fulfil the PBT/vPvB criteria.

[Endocrine disrupting properties:](#)

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1

[SUBSTANCES:](#)

Not applicable (mixture).

3.2

[MIXTURES:](#)

This product is a mixture.

[Chemical description:](#)

Mixture of chemical substances.

[HAZARDOUS INGREDIENTS:](#)

Substances taking part in a percentage higher than the exemption limit:

40 < C < 50 %	Acetone CAS: 67-64-1, EC: 200-662-2, REACH: 01-2119471330-49 CLP: Danger: Flam. Liq. 2:H225 Eye Irrit. 2:H319 STOT SE (narcosis) 3:H336 EUH066	REACH / CLP00	
10 < C < 15 %	n-butyl acetate CAS: 123-86-4, EC: 204-658-1, REACH: 01-2119485493-29 CLP: Warning: Flam. Liq. 3:H226 STOT SE (narcosis) 3:H336 EUH066	REACH / ATP01	
2,5 < C < 5 %	2-methoxy-1-methylethyl acetate CAS: 108-65-6, EC: 203-603-9, REACH: 01-2119475791-29 CLP: Warning: Flam. Liq. 3:H226 STOT SE (narcosis) 3:H336	REACH	
1 < C < 2,5 %	Ethyl alcohol CAS: 64-17-5, EC: 200-578-6, REACH: 01-2119457610-43 CLP: Danger: Flam. Liq. 2:H225 Eye Irrit. 2:H319	REACH	Eye Irrit. 2, H319: C ≥50 %
1 < C < 2,5 %	Trizinc bis(orthophosphate) CAS: 7779-90-0, EC: 231-944-3, REACH: 01-2119485044-40 CLP: Warning: Aquatic Acute 1:H400 (M=1) Aquatic Chronic 1:H410 (M=1)	REACH / CLP00	
1 < C < 2,5 %	Xylene (mixture of isomers) CAS: 1330-20-7, EC: 215-535-7, REACH: 01-2119488216-32 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 (ATE=11000 mg/m3) Acute Tox. (skin) 4:H312 (ATE=1700 mg/kg) Skin Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOT RE 2:H373 Asp. Tox. 1:H304 Aquatic Chronic 3:H412	Autoclassified REACH	
0,1 < C < 0,3 %	4-morpholinecarbaldehyde CAS: 4394-85-8, EC: 224-518-3, REACH: 01-2119987993-12 CLP: Warning: Skin Sens. 1:H317	Autoclassified REACH	

[Impurities:](#)

Does not contain other components or impurities which will influence the classification of the product.

[Stabilizers:](#)

None.

[Reference to other sections:](#)

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

[SUBSTANCES OF VERY HIGH CONCERN \(SVHC\):](#)

List updated by ECHA on 23/01/2024.

[Substances SVHC subject to authorisation, included in Annex XIV of Regulation \(EC\) no. 1907/2006:](#)

None.

[Substances SVHC candidate to be included in Annex XIV of Regulation \(EC\) no. 1907/2006:](#)

None.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.

[POP substances included in the \(EU\) REGULATION 2019/1021~2020/784 on persistent organic pollutants:](#)

None.

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation: 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin:	Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
Eyes: 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. Call a physician immediately.
Ingestion:	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

[Notes to physician:](#)

Treatment should be directed at the control of symptoms and the clinical condition of the patient..

[Antidotes and contraindications:](#)

Specific antidote not known.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

SECTION 5: FIREFIGHTING MEASURES

- 5.1 **EXTINGUISHING MEDIA:**
Extinguishing powder or CO2.
- 5.2 **SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:**
As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide, nitrogen oxides. Exposure to combustion or decomposition products may be a hazard to health.
- 5.3 **ADVICE FOR FIREFIGHTERS:**
Special protective equipment:
Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.
Other recommendations:
Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 **PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:**
Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
- 6.2 **ENVIRONMENTAL PRECAUTIONS:**
Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
- 6.3 **METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:**
Contain and mop up spills with absorbent materials (sawdust, earth, sand, vermiculite, diatomaceous earth, etc..). Keep the remains in a closed container.
- 6.4 **REFERENCE TO OTHER SECTIONS:**
For contact information in case of emergency, see section 1.
For information on safe handling, see section 7.
For exposure controls and personal protection measures, see section 8.
For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

- 7.1 **PRECAUTIONS FOR SAFE HANDLING:**
Comply with the existing legislation on health and safety at work.
- General recommendations:
Avoid any type of leakage or escape. Keep the container tightly closed.
- Recommendations for the prevention of fire and explosion risks:
Not applicable.
- Recommendations for the prevention of toxicological risks:
Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.
- Recommendations for the prevention of environmental contamination:
Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.
- 7.2 **CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**
Forbid the entry to unauthorized persons. Keep out of reach of children. Keep away from sources of heat. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.
- Class of store:
According to current legislation.
- Maximum storage period:
Not available.
- Temperature interval:
min:5 °C, max:25 °C (recommended).
- Incompatible materials:
Keep away from oxidizing agents, acids, metals, alkalis, peroxides.
- Type of packaging:
According to current legislation.
- Limit quantity (Seveso III): Directive 2012/18/EU:
Not applicable (product for non industrial use).
- 7.3 **SPECIFIC END USE(S):**
For the use of this product particular recommendations apart from that already indicated are not available.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

EH40/2005 WELs (United Kingdom) 2018	Year	WEL-TWA		WEL-STEL		Remarks
		ppm	mg/m ³	ppm	mg/m ³	
Acetone	2014	250	594	500	1188	BMGV, A4
n-butyl acetate	2015	50	237	150	713	
2-methoxy-1-methylethyl acetate	-	50	275	100	550	Sk, Recommended
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	1996	-	3	-	-	Breathable dust
Ethyl alcohol	2009	-	-	1000	1880	A3
Trizinc bis(orthophosphate)	1996	-	10	-	-	
Xylene (mixture of isomers)	1996	100	434	150	651	BMGV, A4

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

BMGV - Biological monitoring guidance value. BMGVs are non-statutory and any biological monitoring undertaken in association with a guidance value needs to be conducted on a voluntary basis (ie with the fully informed consent of all concerned).

Sk - Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

A3 - Carcinogenic in animals.

A4 - Non classified as carcinogenic in humans.

- Dermal (Sk):

Means that, in exposures to this substance, the contribution by the cutaneous route, including the mucous membranes and eyes, may result significant for the overall body content if no measures are taken to prevent absorption. There are some chemicals for which dermal absorption, both in liquid and vapour phases, can be very high, and this route of entry may be of equal or greater importance even than the inhalation pathway. In these situations, the use of a biological control is essential in order to quantify the overall amount of contaminant absorbed.

- BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

-

-

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m ³		DNEL Cutaneous mg/kg bw/d		DNEL Oral mg/kg bw/d	
Xylene (mixture of isomers)	289 (a)	77 (c)	s/r (a)	180 (c)	- (a)	- (c)
4-morpholinecarbaldehyde	s/r (a)	98 (c)	s/r (a)	14 (c)	- (a)	- (c)
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)
Trizinc bis(orthophosphate)	s/r (a)	5 (c)	s/r (a)	83 (c)	- (a)	- (c)
Ethyl alcohol	s/r (a)	380 (c)	s/r (a)	343 (c)	- (a)	- (c)
Acetone	- (a)	1210 (c)	- (a)	186 (c)	- (a)	- (c)
n-butyl acetate	960 (a)	480 (c)	11 (a)	11 (c)	- (a)	- (c)
2-methoxy-1-methylethyl acetate	- (a)	275 (c)	- (a)	153,5 (c)	- (a)	- (c)
- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m ³		DNEL Cutaneous mg/cm ²		DNEL Eyes mg/cm ²	
Xylene (mixture of isomers)	289 (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)
4-morpholinecarbaldehyde	s/r (a)	- (c)	s/r (a)	293 (c)	s/r (a)	- (c)
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r (a)	s/r (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
Trizinc bis(orthophosphate)	s/r (a)	s/r (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
Ethyl alcohol	1900 (a)	s/r (c)	s/r (a)	s/r (c)	m/r (a)	- (c)



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

Acetone	2420 (a)	- (c)	- (a)	- (c)	- (a)	- (c)
n-butyl acetate	960 (a)	480 (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
2-methoxy-1-methylethyl acetate	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
- DERIVED NO-EFFECT LEVEL, GENERAL POPULATION:- Systemic effects, acute and chronic:	<u>DNEL Inhalation</u> mg/m3		<u>DNEL Cutaneous</u> mg/kg bw/d		<u>DNEL Eyes</u> mg/kg bw/d	
Xylene (mixture of isomers)	174 (a)	14,8 (c)	s/r (a)	108 (c)	s/r (a)	1, 6 (c)
4-morpholinecarbaldehyde	s/r (a)	29 (c)	s/r (a)	8 (c)	s/r (a)	8 (c)
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r (a)	s/r (c)	s/r (a)	s/r (c)	s/r (a)	s/r (c)
Trizinc bis(orthophosphate)	s/r (a)	2,5 (c)	s/r (a)	83 (c)	s/r (a)	0, 83 (c)
Ethyl alcohol	s/r (a)	114 (c)	s/r (a)	206 (c)	s/r (a)	87 (c)
Acetone	- (a)	200 (c)	- (a)	62 (c)	- (a)	62 (c)
n-butyl acetate	859,7 (a)	102,34 (c)	6 (a)	6 (c)	2 (a)	2 (c)
2-methoxy-1-methylethyl acetate	- (a)	33 (c)	- (a)	54,8 (c)	- (a)	1, 67 (c)
- LOCAL EFFECTS, ACUTE AND CHRONIC:- Local effects, acute and chronic:	<u>DNEL Inhalation</u> mg/m3		<u>DNEL Cutaneous</u> mg/cm2		<u>DNEL Eyes</u> mg/cm2	
Xylene (mixture of isomers)	174 (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)
4-morpholinecarbaldehyde	s/r (a)	- (c)	s/r (a)	176 (c)	s/r (a)	- (c)
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r (a)	s/r (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
Trizinc bis(orthophosphate)	s/r (a)	s/r (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
Ethyl alcohol	950 (a)	s/r (c)	s/r (a)	s/r (c)	m/r (a)	- (c)
Acetone	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
n-butyl acetate	859,7 (a)	102,34 (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
2-methoxy-1-methylethyl acetate	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

m/r - DNEL not derived (medium hazard).

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

- <u>PREDICTED NO-EFFECT CONCENTRATION, AQUATIC ORGANISMS:- Fresh water, marine water and intermittent release:</u>	<u>PNEC Fresh water</u> mg/l		<u>PNEC Marine</u> mg/l		<u>PNEC Intermittent</u> mg/l	
Xylene (mixture of isomers)	0.327		0.327		0.327	
4-morpholinecarbaldehyde	0.5		0.05		5	
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r		s/r		s/r	
Trizinc bis(orthophosphate)	0.0206		0.0061		-	
Ethyl alcohol	0.96		0.79		2.75	
Acetone	10.6		1.06		21	
n-butyl acetate	0.18		0.018		0.36	
2-methoxy-1-methylethyl acetate	0.635		0.0635		6.35	
- <u>WASTEWATER TREATMENT PLANTS (STP) AND SEDIMENTS IN FRESH- AND MARINE WATER:</u>	<u>PNEC STP</u> mg/l		<u>PNEC Sediments</u> mg/kg dw/d		<u>PNEC Sediments</u> mg/kg dw/d	
Xylene (mixture of isomers)	6.58		12.46		12.46	
4-morpholinecarbaldehyde	2000		2.69		0.269	
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r		s/r		s/r	
Trizinc bis(orthophosphate)	0.1		117.8		56.5	
Ethyl alcohol	580		3.6		2.9	
Acetone	100		30.4		3.04	
n-butyl acetate	35.6		0.981		0.0981	
2-methoxy-1-methylethyl acetate	100		3.29		0.329	
- <u>PREDICTED NO-EFFECT CONCENTRATION, TERRESTRIAL ORGANISMS:- Air, soil and effects for predators and humans:</u>	<u>PNEC Air</u> mg/m3		<u>PNEC Soil</u> mg/kg dw/d		<u>PNEC Oral</u> mg/kg dw/d	
Xylene (mixture of isomers)	-		2.31		-	
4-morpholinecarbaldehyde	-		0.244		-	
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	s/r		s/r		n/b	



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

Trizinc bis(orthophosphate)	-	35.6	n/b
Ethyl alcohol	s/r	0.63	720
Acetone	-	29.5	n/b
n-butyl acetate	s/r	0.0903	n/b
2-methoxy-1-methylethyl acetate	-	0.29	-

(-) - PNEC not available (without data of registration REACH).

n/b - PNEC not derived (not bioaccumulative potential).

s/r - PNEC not derived (not identified hazard).

8.2

EXPOSURE CONTROLS:**ENGINEERING MEASURES:**

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

- Protection of respiratory system:

Avoid the inhalation of vapours.

- Protection of eyes and face:

It is recommended to install water taps or sources with clean water close to the working area.

- Protection of hands and skin:

It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Mask: 	✓	AX-type filter mask (brown) for gases and vapours of organic compounds with a boiling point less or equal to 65°C (EN14387), with single-use filters. Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.
Safety goggles: 	✓	Safety goggles with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:		No.
Gloves: 	✓	Gloves resistant against chemicals (EN374). There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:		No.
Apron:		No.
Clothing:		Advisable.

- Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment of the product, wastes, packages or spraybooth sewages.

- Spills on the soil:

Prevent contamination of soil.

- Spills in water:

Do not allow to escape into drains, sewers or water courses.

-Water Management Act:

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

VOC (product ready for use*):



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: VEHICLE REFINISHING PRODUCTS (defined in the Directive 2004/42/EC, Annex I.2): Emission subcategory B) Bodyfiller. VOC (product ready for use*): (QUICK 1K EASY FILLER SPRAY WHITE Cod. 5011-001060 = 100 in volume): 687,2 g/l* (VOC max.250 g/l* starting from 01.01.2010)

VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 89,86 % Weight, VOC (supply): 76,30 % Weight, VOC: 58,11 % C (expressed as carbon), Molecular weight (average): 94,48 , Number C atoms (average): 6,00

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:Appearance

Physical state:	Aerosol
Colour:	White
Odour:	Characteristic
Odour threshold:	Not available (mixture).

Change of state

Melting point:	Not available (mixture).
Initial boiling point:	56,2* °C at 760 mmHg

- Flammability:

Flashpoint:	Not available.
Lower/upper flammability or explosive limits:	1,20 - 13,00 % Volume 25°C
Autoignition temperature:	365 °C

Stability

Decomposition temperature:	Not available (technical impossibility to obtain the data).
----------------------------	---

pH-value

pH:	Not applicable (non-aqueous media).
-----	-------------------------------------

- Viscosity:

Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Viscosity (flow time):	Not available.

- Solubility(ies):

Solubility in water	Not available
Liposolubility:	Not applicable (inorganic product).
Partition coefficient: n-octanol/water:	Not applicable (mixture).

- Volatility:

Vapour pressure:	8300 hPa at 20°C
Evaporation rate:	Not available (lack of data).

Density

Relative density:	0,900 at 20/4°C	Relative water
Relative vapour density:	2,01* at 20°C 1 atm.	Relative air

Particle characteristics

Particle size:	Not available.
----------------	----------------

- Explosive properties:

Not available.

- Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:Information regarding physical hazard classes

Aerosol sprays:	Extremely flammable aerosol.
-----------------	------------------------------

Other security features:

Heat of combustion:	7466 Kcal/kg	
VOC (supply):	76,3 % Weight	
VOC (supply):	687,2 g/l	
Nonvolatile:	-9,999,00 % Weight	1h. 60°C

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

SECTION 10: STABILITY AND REACTIVITY

10.1	REACTIVITY: - Corrosivity to metals: It is not corrosive to metals. - Pyrophorical properties: It is not pyrophoric.
10.2	CHEMICAL STABILITY: Stable under recommended storage and handling conditions.
10.3	POSSIBILITY OF HAZARDOUS REACTIONS: Possible dangerous reaction with oxidizing agents, acids, metals, alkalis, peroxides.
10.4	CONDITIONS TO AVOID: - Heat: Keep away from sources of heat. - Light: If possible, avoid direct contact with sunlight. - Air: The product is not affected by exposure to air, but should not be left the containers open. - Humidity: Avoid extreme humidity conditions. - Pressure: Not relevant. - Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.
10.5	INCOMPATIBLE MATERIALS: Keep away from oxidizing agents, acids, metals, alkalis, peroxides.
10.6	HAZARDOUS DECOMPOSITION PRODUCTS: As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2022/692 (CLP).				
11.1	INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 : ACUTE TOXICITY:			
	Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m ³ ·4h Inhalation
	Xylene (mixture of isomers)	4300 Rat	1700 Rabbit	> 22080 Rat
	4-morpholinecarbaldehyde	7360 Rat	18400 Rabbit	
	Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	7500 Rat	> 2000 Rabbit	> 6820 Rat
	Trizinc bis(orthophosphate)	> 5000 Rat		> 5410 Rat
	Ethyl alcohol	8300 Rat	> 20000 Rabbit	> 20000 Rat
	Acetone	5800 Rat	7426 Rabbit	> 76000 Rat
	n-butyl acetate	10768 Rat	17600 Rabbit	> 23400 Rat
	2-methoxy-1-methylethyl acetate	8532 Rat	> 5000 Rat	> 35700 Rat
	Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m ³ ·4h Inhalation
	Xylene (mixture of isomers)	-	*1700	11000 Vapours
	Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	-	-	6820
	Trizinc bis(orthophosphate)	-	-	5410
	Ethyl alcohol	-	-	-
	Acetone	-	-	76000 Vapours
	n-butyl acetate	-	-	23400 Vapours
	2-methoxy-1-methylethyl acetate	-	-	35700 Vapours
(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results. (-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.				
	- No observed adverse effect level	NOAEL Oral mg/kg bw/d	NOAEL Cutaneous mg/kg bw/d	NOAEC Inhalation mg/m ³
	Ethyl alcohol	1730 Rat		



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

- Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 2000 mg/kg bw	Not available.	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Respiratory corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Cutaneous:	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.
- Neurological:	SE 	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

Does not harm fertility. Does not harm the unborn child.

- Effects via lactation:

Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

- Short-term exposure:

May irritate the eyes and skin. May cause drowsiness or dizziness.

- Long-term or repeated exposure:

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated exposure may cause skin dryness or cracking.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOKINETICS, METABOLISM AND DISTRIBUTION:- Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: Xylene (mixture of isomers), 2-methoxy-1-methylethyl acetate.

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

Not available.

11.2 INFORMATION ON OTHER HAZARDS:Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

Other information:

No additional information available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2022/692 (CLP).

12.1 TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours
Xylene (mixture of isomers)	14 - Fishes	16 - Daphniae	10 - Algae
4-morpholinecarbaldehyde	500 - Fishes	500 - Daphniae	23880 - Algae
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)	100 - Fishes	100 - Daphniae	100 - Algae
Trizinc bis(orthophosphate)	0.27 - Fishes	0.14 - Daphniae	0.26 - Algae
Ethyl alcohol	11200 - Fishes	5012 - Daphniae	275 - Algae
Acetone	5540 - Fishes	12100 - Daphniae	
n-butyl acetate	18 - Fishes	44 - Daphniae	675 - Algae
2-methoxy-1-methylethyl acetate	134 - Fishes	408 - Daphniae	1000 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours
Ethyl alcohol	250 - Fishes	9.6 - Daphniae	12 - Algae
n-butyl acetate		23 - Daphniae	
2-methoxy-1-methylethyl acetate		100 - Daphniae	

- Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:	Cat.3	HARMFUL: Harmful to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

12.2 PERSISTENCE AND DEGRADABILITY:- Biodegradability:

Not available.

Aerobic biodegradation for individual ingredients	COD mgO ₂ /g	%DBO/DQO			Biodegradabilidad
		5 days	14 days	28 days	
Xylene (mixture of isomers)	2620	52	81	88	Easy
4-morpholinecarbaldehyde		-	2	96	Easy
Ethyl alcohol	1999	74	95	99	Easy
Acetone	1920	87	-	91	Easy
n-butyl acetate	2204	80	82	83	Easy
2-methoxy-1-methylethyl acetate	1520	22	78	90	Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

- Hydrolysis:

Not available.

- Photodegradability:

Not available.

12.3 BIOACCUMULATIVE POTENTIAL:

May bioaccumulate.

Bioaccumulation for individual ingredients	logPow	BCF L/kg	Potential
Xylene (mixture of isomers)	3.16	56.5 (calculated)	Low
4-morpholinecarbaldehyde	-1.2	3.2 (calculated)	No bioaccumulable
Titanium dioxide (as a powder containing 1% or more of particles with an aerodynamic diameter ≤ 10 µm)			Not available
Trizinc bis(orthophosphate)			Not available
Ethyl alcohol	-0.35	3.2 (calculated)	No bioaccumulable
Acetone	-0.24	3.2 (calculated)	No bioaccumulable
n-butyl acetate	1.81	6.9 (calculated)	No bioaccumulable
2-methoxy-1-methylethyl acetate	0.56	3.2 (calculated)	No bioaccumulable

12.4 MOBILITY IN SOIL:

Not available

Mobility for individual ingredients	log P _{oc}	Constant of Henry Pa·m ³ /mol 20°C	Potential
4-morpholinecarbaldehyde	-0,17		No bioaccumulable
Ethyl alcohol	0,2		No bioaccumulable
Acetone	0,99	3 (calculated)	No bioaccumulable
n-butyl acetate	1,84	28,5 (calculated)	No bioaccumulable
2-methoxy-1-methylethyl acetate	0,23	0,42 (calculated)	No bioaccumulable
Xylene (mixture of isomers)	2,25	660 (calculated)	Low

12.5 RESULTS OF PBT AND VPVB ASSESMENT:(Annex XIII of Regulation (EC) no. 1907/2006:)

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 ENDOCRINE DISRUPTING PROPERTIES:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

12.7 OTHER ADVERSE EFFECTS:- Ozone depletion potential:

Not available.

- Photochemical ozone creation potential:

Not available.

- Earth global warming potential:In case of fire or incineration liberates CO₂.**SECTION 13: DISPOSAL CONSIDERATIONS**13.1 WASTE TREATMENT METHODS:Directive 2008/98/EC~Regulation (EU) no. 1357/2014:

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

LER code	Description	Type of waste
		Hazardous

Type of waste according to Regulation (EU) No. 1357/2014:

HP 4 Irritant — skin irritation and eye damage
HP 14 Ecotoxic



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 UN NUMBER OR ID NUMBER:

1950

14.2 UN PROPER SHIPPING NAME:

AEROSOLS

14.3 TRANSPORT HAZARD CLASS(ES):

Transport by road (ADR 2023) and
Transport by rail (RID 2023):

- Class: 2
- Packing group:
- Classification code: 5F
- Tunnel restriction code: (D)
- Transport category: 2, max. ADR 1.1.3.6. 333 L
- Limited quantities: 1 L (see total exemptions ADR 3.4)
- Transport document: Consignment paper.
- Instructions in writing: ADR 5.4.3.4



Transport by sea (IMDG 40-20):

- Class: 2
- Packing group:
- Emergency Sheet (EmS): F-D,S-U
- First Aid Guide (MFAG): 620*
- Marine pollutant: No.
- Transport document: Shipping Bill of lading.



Transport by air (ICAO/IATA 2021):

- Class: 2
- Packing group:
- Transport document: Air Bill of lading.



Transport by inland waterways (ADN):

Not available

14.4 PACKING GROUP:

See section 14.3

14.5 ENVIRONMENTAL HAZARDS:

Not applicable.

14.6 SPECIAL PRECAUTIONS FOR USER:

Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

14.7 MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:

Not available.



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use:

See section 1.2

Tactile warning of danger:

Not applicable (the classification criteria are not met).

Child safety protection:

Not applicable (the classification criteria are not met).

VOC information on the label:

Contains VOC max. 687,2 g/l* for the product ready for use - The limit value 2004/42/EC-IIB cat. B) Bodyfiller. is VOC max. 250 g/l

ANNEX II: REPORTABLE EXPLOSIVES PRECURSORS

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

OTHER REGULATIONS:

Not available.

Control of the risks inherent in major accidents (Seveso III):

See section 7.2

Other local legislations:

The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETY ASSESSMENT:

A chemical safety assessment has not been carried out for this mixture.

SECTION 16 : OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2022/692 (CLP), Annex III:

H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H351i Suspected of causing cancer if inhaled. H373 May cause damage to hearing organs through prolonged or repeated exposure if inhaled. H229 Pressurised container: may burst if heated.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2021).
- European agreement on the international carriage of dangerous goods by road, (ADR 2023).
- International Maritime Dangerous Goods Code IMDG including Amendment 40-20 (IMO, 2020).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangeous goods by road.
- RID: Regulations concerning the international transport of dangeous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.

SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2020/878



QUICK 1K EASY FILLER SPRAY WHITE

Code : 5011-001060



Version: 1

Date of issue: 05/06/2024

Date of printing: 05/06/2024

· ICAO: International Civil Aviation Organization.

[SAFETY DATA SHEET REGULATIONS:](#)

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

[HISTORIC:](#) [REVISION:](#)

Version: 1 05/06/2024

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.